

Form 9-331
Dec. 1973

O.C.D. COPY

Form Approved.
Budget Bureau No. 42-R1424

AMENDED REPORT
EFFECTIVE 7-7-80

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FNL & 1980' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

☒
☒
☐
☐
☐
☐
☐
☐

5. LEASE

NM-14118

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

FEB 23 1981

8. FARM OR LEASE NAME

Allison CQ Federal

9. WELL NO.

5

10. FIELD OR WILDCAT NAME

Boyd Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unit C, Sec. 13-19S-24E

12. COUNTY OR PARISH

13. STATE

Eddy

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 9320'; WLPBTD 9290' WIH w/Tubing Conveyed gun & Baker Lok-Set packer on 2-7/8" tubing set packer at 8916'. Perforated 8950-8960' w/40 .50" holes (4spf). No GTS. Ran swab & swabbed dry. Had trace of gas TSTM. Pulled guns. WIH w/Baker Lok-Set packer on 2-7/8" tubing, set packer at 8920'. Acidized perforations w/2500 gallons 7½% MS acid & nitrogen w/ball sealers. Sand frac'd w/16000g treated fluid, 8000g CO-2 & 50000# sand. Swabbed dry in 3 runs. Well stabilized at 90# on 1/8" choke. Killed well, pulled packer out of hole at 8920. RIH w/RBP set at 8930'. WIH w/casing gun on wireline & perforated 8804-8904 w/14 .50" holes as follows: 8804, 05, 06, 17, 17½, 18, 18½, 19, 8898, 99, 8901, 02, 03 & 04. POOH. RIH w/Guiberson Uni VI packer, set packer at 8775'. Swabbed dry. Acidized perforations w/2500 gallons 7½% acid & nitrogen. Flowing 30# on 1/2" choke. Sand frac'd perforations w/16000g gelled 3% acid & 8000 gallons CO-2 & 19000# sand, w/ball sealers. Flowing back load. Well cleaned up and flowed 90# on 1/2" choke.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Wanda Howell TITLE Engineering Secretary

DATE 2-17-81

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY:

DATE

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

ACCEPTED FOR RECORD

FEB 20 1981

1981 C 5634

SECRET