

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Gates Ref. Corp.</u>		Lease <u>SPC KZ State</u>		Well # <u>6</u>	
Location of Well	Unit <u>C</u> <u>660 N</u> <u>1980 W</u>	Section <u>1</u>	Township <u>19</u>	Range <u>24</u>	County <u>Eddy</u>
Drilling Contractor	<u>Jandis Drilling Co</u>		Type of Equipment <u>Rotary -</u>		

** witness* APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2"</u>	<u>13 3/8"</u>	<u>48</u>		<u>400</u>	<u>300 ctn.</u>
<u>12 1/4"</u>	<u>8 7/8"</u>	<u>24</u>		<u>900</u>	<u>500 "</u>
<u>7 7/8"</u>	<u>5 1/2 or 4 1/2"</u>	<u>15.5-17</u> <u>10.5-11.6</u>		<u>9200</u>	<u>300</u>

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____
(Approved) (Rejected) _____

Inspected by _____ date _____

Cementing Program

Size of hole 12 1/4 Size of Casing 8 5/8 Sacks cement required _____

Type of Shoe used guide Float collar used Insert Btm 3 jts welded yes

TD of hole 1005' Set 1005' Feet of 8 5/8 Inch 24 # Grade J-55

New-used csg. @ 1005' with 150 sacks neat cement around shoe
+ 500 sax Hall's Lite additives 270cc

Plug down @ 11:00 (AM) (PM) Date _____

Cement circulated yes No. of Sacks _____

Cemented by _____ Witnessed by _____

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____

Full returns

centralizer @ 975' last day back @ 900'