

DISTRIBUTION		
SANTA FE	1	
FILE	1	✓
U.S.G.S.		
LAND OFFICE		
OPERATOR	1	

N MEXICO OIL CONSERVATION COMMISSION

Supersedes Old  
C-102 and C-103  
Effective 1-1-65

MAR 13 1980

O. C. D.

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name SRC "KZ" State
9. Well No. 1 6
10. Field and Pool, or Wildcat Und Penasco Draw Morrow
12. County Eddy

SUNDY NOTICES AND REPORTS ON WELLS OFFICE  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☒ OTHER-

2. Name of Operator  
Yates Petroleum Corporation ✓

3. Address of Operator  
207 South 4th Street - Artesia, NM 88210

4. Location of Well  
UNIT LETTER C 660 FEET FROM THE North LINE AND 1980 FEET FROM  
THE West LINE, SECTION 1 TOWNSHIP 19S RANGE 24E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)  
3684' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 17½" hole at 5:00 PM 3-5-80.

TD 406' - Ran 11 joints of 13-3/8" 54.5# ST&C (411') of casing set at 406'.  
1-Texas Pattern Guide Shoe at 406', Insert float at 368'. Cemented w/400  
sacks of Class C 4% CaCl. PD 10:30 PM 3-6-80. WOC 12 hours, backed off,  
reduced hole to 12¼", drilled plug and tested to 600# OK and resumed drilling.

TD 1005' - Ran 25 joints of 8-5/8" 24# J-55 LT&C (1008') of casing set at  
1003', 1-Guide Shoe at 1003', Insert Float at 963'. Cemented w/500 sacks  
Howco, 2% CaCl, tailed in w/150 sacks Class C 2% CaCl. PD 11:00 PM 3-8-80.  
Cement circulated 100 sacks to surface. WOC 18 hours; NU and tested to 1500#  
OK, reduced hole to 7-7/8", drilled plug and tested to 600# OK. Resumed  
drilling.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Christine Tomlinson</u>	TITLE <u>Geol. Secty.</u>	DATE <u>3-12-80</u>
APPROVED BY <u>W. A. Gussitt</u>	TITLE <u>SUPERVISOR, DISTRICT 2</u>	DATE <u>MAR 14 1980</u>
CONDITIONS OF APPROVAL, IF ANY:		