

The form is to be filed with the appropriate District Office of the Commission not later than 30 days after the completion of any new test run or completed well. It is to be accompanied by a copy of all electrical and radio-activity logs run in the well and a summary of all special tests, including permeability tests. All depths reported shall be measured together in the case of partially drilled wells, true vertical depth shall also be reported. For multiple completions, Items 25 through 34 shall be reported for each zone. The form is to be filed in quadruplicate except on Form 1423, where six copies are required. See Rule 1423.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Ark.		T. Canyon		T. Ojo Alamo		T. Penn. "B"	
T. Salt	320'	T. Strawn		T. Kirtland-Fruitland		T. Penn. "C"	
T. Salt	1060'	T. Atoka		T. Fractured Cliffs		T. Penn. "D"	
T. Yates	1245'	T. Miss.		T. Cliff House		T. Leadville	
T. T. Rivers	1640'	T. Devonian		T. Monfort		T. Madison	
T. Queen	2228'	T. Silurian		T. Point Lookout		T. Elbert	
T. Gracburg	2620'	T. Miocene		T. Mancos		T. McCracken	
T. San Andres	3082'	T. Simpson		T. Gallup		T. Ignacio Quiz	
T. Glorieta		T. McKee		Base Greenhorn		T. Granite	
T. Faddock		T. Ellenburger		T. Dakota		T.	
T. Bluebird		T. Gr. Wash.		T. Morrison		T.	
T. Tubb		T. Granite		T. Todilite		T.	
T. Drinkard		T. Delaware Sand		T. Entrada		T.	
T. Abo		T. Bone Springs		T. Wingate		T.	
T. Wolfcamp		T.		T. Chinle		T.	
T. Penn.		T.		T. Permian		T.	
T. Cisco (Bough Cr.)		T.		T. Penn. "A"		T.	

OIL OR GAS SANDS OR ZONES

No. 1, from	1640'	to	1740'	No. 4, from		to	
No. 2, from	2400'	to	2558'	No. 5, from		to	
No. 3, from	2940'	to	3010'	No. 6, from		to	

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from		to		feet.	
No. 2, from		to		feet.	
No. 3, from		to		feet.	
No. 4, from		to		feet.	

FORMATION RECORD Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0'	320'	320	Redbed				
320'	1060'	740	Salt				
1060'	1640'	580	Anhydrite				
1640'	2228'	588	Sand & Lime				
2228'	2620'	392	Sand				
2620'	3082'	462	Sand & Lime				
3082'	3200'	118	Lime				