

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates Petr. Corp.</u>		Lease <u>Greewood BD State</u>		Well # <u>5</u>	
Location of Well	Unit <u>2310 N</u> <u>2310 W</u>	Section <u>6</u>	Township <u>19</u>	Range <u>75</u>	County <u>El Paso</u>
Drilling Contractor	<u>Cactus Drilling Co.</u>		Type of Equipment <u>Rotary</u>		

* witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
15"	10 3/4"	32.75		320	275 lbs
9 5/8"	7"	20		1000	500 lbs
6 1/4"	4 1/2"	9.5		3150	200 lbs

Casing Data:

Surface 24 joints of 7 inch 20 # Grade J-55

yes

(Approved) (Rejected)

Inspected by BW Weaver date 3-1-80

Cementing Program

Size of hole 9 7/8 Size of Casing 7 Sacks cement required 100

Type of Shoe used Guide Float collar used Insert Btm 3 jts welded yes

TD of hole 973 Set 985 Feet of 7 Inch 20 # Grade J-55

New-used csg. @ 985 with 100 sacks neat cement around shoe

+ 400 sax Hawco Lite additives #5 Gilsomite 1/4 LB Flo seal 2 1/2 CC

Plug down @ 8:00 (AM) (PM) Date 3-1-80

Cement circulated yes No. of Sacks 50 SX

Cemented by Hawco Witnessed by BW Weaver

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: Less Circulation @ 695