

SANTA FE	1	
FILE	1	✓
U.S.G.S.		
LAND OFFICE		
OPERATOR	1	

NEW MEXICO OIL CONSERVATION COMMISSION
RECEIVED

Supplemental to
C-102 and C-103
Effective 1-1-65

MAR 20 1980

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. 04-783	
7. Unit Agreement Name	
8. Farm or Lease Name Greasewood BD State	
9. Well No. 1 5	
10. Field and Pool, or Wildcat Penasco Draw SA Yeso	
ASSOC	
12. County Eddy	

SUNDY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REPER OR PLUG BACK AN ABANDONED RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator
Yates Petroleum Corporation ✓

Address of Operator
207 South 4th Street - Artesia, NM.

Location of Well
UNIT LETTER F 2310 FEET FROM THE North LINE AND 2310 FEET FROM
THE West LINE, SECTION 6 TOWNSHIP 19S RANGE 25E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
3641'

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>		COMMENCE DRILLING OPS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
WELL OR ALTER CASING <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	
OTHER <input type="checkbox"/>		OTHER <input type="checkbox"/>	

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 14-3/4" hole at 7:00 PM 2-28-80.

TD 320' - Ran 8 joints of 10-3/4" 32.75# H-40 ST&C (322') of casing set at 320'. 1-guide shoe at 320'. 1-insert float at 280'. Cemented w/275 sacks of Class C 4% CaCl. PD 6:55 AM 2-29-80. Circulated 60 sacks of cement to surface. WOC 12 hours, cut off, reduced hole to 9-5/8", drilled plug and tested to 600# Ok and resumed drilling.

TD 985' - Ran 24 joints of 7" 20# K-55 (972' & 1 sub) of casing set at 985'. 1-guide shoe at 985', 1-insert float at 945'. Cemented w/400 sacks Howco Lite, 5#/sack gilsonite, 1/4#/sack flocele, 2% CaCl. Followed w/100 sacks Class C 2% CaCl. PD 7:10 PM 3-1-80. Circulated 50 sacks of cement to the surface. WOC 18 hours, nipples up and tested to 1000#. OK. Reduced hole to 6 1/4", drilled plug and tested to 600# OK and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

WED <u>Christina Tombarco</u>	TITLE <u>Geol. Secty.</u>	DATE <u>3-19-80</u>
APPROVED BY <u>W.A. Gressett</u>	TITLE <u>SUPERVISOR, DISTRICT II</u>	DATE <u>MAR 24 1980</u>
CONDITIONS OF APPROVAL, IF ANY:		