

DISTRIBUTION		
SANTA FE	1	
FILE	1	✓
U.S.G.S.		
LAND OFFICE		
OPERATOR	1	

MEXICO OIL CONSERVATION COMMISSIC

Supersedes Old
C-102 and C-103
Effective 1-1-65

RECEIVED

APR 2 1980

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. OG-783
7. Unit Agreement Name
8. Farm or Lease Name Greasewood BD State
9. Well No. 1 6
10. Field and Pool or Voluntary Penasco Draw SA Yeso (Assoc)
12. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS, C. D.
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
Yates Petroleum Corporation

3. Address of Operator
207 South 4th Street - Artesia, NM 88210.

4. Location of Well
UNIT LETTER B 990 FEET FROM THE North LINE AND 1650 FEET FROM THE East LINE, SECTION 6 TOWNSHIP 19S RANGE 25E NMPH.

15. Elevation (Show whether DF, RT, GR, etc.)
3632' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 14-3/4" hole at 7:00 PM 3-23-80.
TD 320' - Ran 8 joints of 10-3/4" 30# K-55 (322') of casing set at 320'.
 1-guide shoe at 320' and 1-insert float at 280'. Cemented w/300 sacks Class "C" 4% CaCl. PD 11:15 AM 3-24-80. Cement circulated 30 sacks to surface. WOC 12 hours, backed off and reduced hole to 9-7/8", drilled plug and tested to 600#. OK. Resumed drilling.
TD 1007' - Ran 25 joints of 7" 20# J-55 (1007') of casing set at 1007'.
 1-regular pattern guide shoe at 1007', 1-flapper float shoe at 967'. Cemented w/Dowell w/450 sacks 65-35 Lite Poz, 4% D-20 Bentonite, 8# D-42 Kolite, 1/4# D-29 celloflakes, 3% 5-1 CaCl. Followed w/150 sacks Class "C" 3% 5-1 CaCl. Circulated 45 sacks of cement to surface. PD 10:45 AM 3-26-80. WOC 18 hours, NU and tested to 1000#. OK. Reduced hole to 6 1/4", drilled plug and tested to 600# OK and resumed drilling.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

CHD. Christine Johnson TITLE Geol. Secty. DATE 4-2-80

PROVED BY W.A. Gessert TITLE SUPERVISOR, DISTRICT II DATE APR 2 1980

CONDITIONS OF APPROVAL, IF ANY: