

ARTESIA OIL COMPANY FIELD REPORT
DRAWN BY
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Garrett Energy Inc.</u>		Lease <u>Beverly State</u>		Well # <u>1</u>	
Location of Well	Unit <u>19805</u> <u>66003</u>	Section <u>2</u>	Township <u>19</u>	Range <u>27</u>	County <u>Eddy</u>
Drilling Contractor	<u>Yucca Dry Co</u> <u>Watson Dry Co.</u>		Type of Equipment <u>Rotary to start approx 225-80</u>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>11</u>	<u>8 3/8"</u>	<u>24 #</u>		<u>337</u> <u>400</u>	<u>75 ctn.</u>
<u>7 7/8"</u>	<u>5.12"</u>	<u>14 #</u>		<u>2600</u>	<u>250 ctn.</u>

Casing Data:

Surface joints of 3 3/8 inch 24 # Grade J-55
(Approved) (Rejected)

Inspected by M.S. date 3/4/80

Cementing Program

Size of hole 11" Size of Casing 8 3/8 Sacks cement required

Type of Shoe used guide Float collar used Insert Btm 3 jts welded yes

TD of hole 337 Set 337 Feet of 8 3/8 inch 24 # Grade J-55

New-used csg. @ 337 with 150 sacks neat cement around shoe

+ sack additives

Plug down @ 9:00 (AM) (PM) Date 3/4/80

Cement circulated yes No. of Sacks 150x

Cemented by Holtzhausen Witnessed by

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks:

centralizers a 297'-257'