

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.O.B.	
LAND OFFICE	
OPERATOR	1

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. L-4379

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REFINER OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT TO DRILL" FORM FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	7. Unit Agreement Name
2. Name of Operator Garrett Energy, Inc.	8. Farm or Lease Name Beverly State
3. Address of Operator P.O. Box 798, Artesia, New Mexico 88210	9. Well No. #1
4. Location of Well UNIT LETTER <u>L</u> <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>2</u> TOWNSHIP <u>19S</u> RANGE <u>27E</u> N.M.P.M.	10. Field and Pool, or Wildcat Und. Artesia On. G. SA
11. Elevation (Show whether DF, RT, GR, etc.) 3494.9 GL	12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

March 1, 1980: Spudded 8:00 a.m. with 11" bit.

March 5, 1980: Ran 334' of 8 5/8", 24# casing. Cemented with 150 Sxs. Class "C" cement with 2% CaCl. Cement circulated 15 Sxs. to pits. WOC 18 hours. 1000# pressure - 30 minutes.

March 9, 1980: Ran 1750' of 4 1/2", 9 1/2# casing. Cement with 115 Sxs. Class "C" cement with 2% CaCl.

NOTE: 5 1/2" casing was not available at the time of running casing. Therefore, 4 1/2" was used.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Shere M. Cook TITLE Secretary DATE 3/26/80  
APPROVED BY W. A. Gussert TITLE SUPERVISOR, DISTRICT II DATE APR 11 1980  
CONDITIONS OF APPROVAL, IF ANY: