

Form 9-331  
Dec. 1973Form Approved.  
Budget Bureau No. 42-R1424UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐  
well well

2. NAME OF OPERATOR  
Yates Petroleum Corporation ✓

3. ADDRESS OF OPERATOR  
207 So. 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1650' FSL & 990' FWL of Sec. 1-  
AT SURFACE: 19S-24E  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input checked="" type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input checked="" type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>
(other)			

5. LEASE  
NM-0439491

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Federal "CW"-B

9. WELL NO.  
4

10. FIELD OR WILDCAT NAME  
Penasco Draw SA Yeso Associated

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Unit L-Sec. 1-19S-24E

12. COUNTY OR PARISH  
Eddy

13. STATE  
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3679' GR

RECEIVED

OCT 16 1980

O. C. D.  
ARTESIA, OFFICE

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

TD 3100' - WIH w/Steel Strip gun on wireline and perforated 2663-2712' w/10 .50" holes as follows: 2663, 71, 73, 2690, 95, 98, 2700, 07, 09, & 12'. RIH w/2-3/8" tubing to 2739'. Spotted acid over perforations. Treated perms w/1500 gallons 15% HCL, 30000 gallons gelled 1% KCL water & 45000# sand. Bled well down. RBIH w/Steel Strip gun on wireline and perforated 2494-2583' w/12 .50" holes as follows: 2494, 2501, 28, 32-1/2, 55, 58, 61, 63-1/2, 67, 71, 80, 83'. Ran tubing w/RBP to 2621'. Set RBP at 2621'. Spotted acid over perforations. Treated w/1500 gallons 15% HCL, 30000 gallons gelled water, 45000# sand.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Albert K. Hall TITLE Engineer DATE October 3, 1980

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

OCT 14 1980

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO