

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> For <input type="checkbox"/>
5. State Oil & Gas Lease No. B-8876

SUNDRY NOTICES AND REPORTS ON WELLS RECEIVED  
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.

OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	MAR 6 1980
Name of Operator Marbob Energy Corp.	O. C. D.
Address of Operator P.O. Box 304, Artesia, N.M. 88210	ARTESIA, OFFICE
Location of Well UNIT LETTER H 2310 FEET FROM THE North LINE AND 330 FEET FROM THE East LINE, SECTION 3 TOWNSHIP 19S RANGE 29E N.M.P.M.	

7. Unit Agreement Name Turkey Track Sec. 3 Ut.
8. Farm or Lease Name Turkey Track Sec. 3 Ut.
9. Well No. 21
10. Field and Pool, or Wildcat Turkey Track SR Qn Grbg
12. County Eddy

15. Elevation (Show whether DF, RT, GR, etc.)  
3397 GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPERATIONS <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
WILL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3-3-80  
Spudded 2:00 p.m. Drilled 339' of 12 1/4" hole, pumped mud to sweep hole & pulled out. Ran Texas pattern shoe & insert float & 8 jts. 8 5/8" 20# new casing, landed @ 323.14' GR & 335.14' KB, pumped 200 sax Class C 2% calcium chloride, plug down @ 10:00 p.m.. Lost circulation @ 40', ready mixed to surface w/8 yds. WOC 18 hrs.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

ED Carolyn Davis TITLE Secretary DATE 3/5/80

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: