

NO. OF COPIES RECEIVED

DISTRIBUTION

SANTA FE

FILE

U.S.G.S.

LAND OFFICE

OPERATOR

NEW MEXICO OIL CONSERVATION COMMISSION
WELL COMPLETION OR RECOMPLETION REPORT AND LOG

RECEIVED

APR 11 1980

Form O-185
Revised 11-1-78

1. Indicate Type of Lease
State ☒ Free ☐

2. Lease No. or Lease No.
B-8876

3. Well Name
Turkey Track Sec 3 Ut

4. Well Name
Turkey Track Sec 3 Ut

5. Well No.
21

6. Well Name, Block, or Well
Turkey Track SR-Q-G

7. County
Eddy

8. TYPE OF WELL
OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐

9. TYPE OF COMPLETION
NEW WELL ☒ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ RE-ENTRY ☐ OTHER ☐

10. Marbob Energy Corp. ✓

11. Address to permit
P.O. Box 304, Artesia, N.M. 88210

12. LETTER H LOCATED 2310 FEET FROM THE North LINE AND 330 FEET FROM

13. East LINE OF SEC. 3 TWP. 19S RGE. 29E

14. Date Drilled 3/3/80 15. Date Test Borehole 3/10/80 16. Date Comp. Ready to Prod. 3/26/80 17. Flowing in (DL, RKB, RI, GR, etc.) 3397 GR 18. Flow, Casinghead 3397 GR

19. Depth 3000' 20. Plug Back Test 2974' 21. If Multiple Casing, How Many 22. Interval Drilled by 23. Rotary Tools X 24. Cable Tools

25. Interval, Casing Completion (Top, Bottom, None) 2170-2548' Queen; 2590-2892' Grayburg

26. Type of Test (Indicate if is full) Gamma ray neutron 27. Was Directional Survey Made Yes 28. Was Well Cased No

CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB. FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	20#	323.14'	12 1/4"	200 sax Class C 2% CC	
4 1/2"	10.50#	3000'	7 7/8"	425 sax Class H, 5/10 of 1% CFR-2	
				5# salt, 10# sand per sack	

LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN

TUBING RECORD

SIZE	DEPTH SET	PACKER SET
2 3/8"	2912'	

29. Acid, Shot, Fracture, Cement Squeeze, ETC.

DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
2170-2892	5500 bbl gel water, 134,000# 20/40 sand, 80,000# 10/20 sand

30. PRODUCTION

31. Production Method (Flow log, gas lift, pumping - Size and type pump) Pumping - 1 1/2"

32. Well Status (Prod. or Shut-in) Prod.

33. Date First Production 4/1/80

34. Date of Test 3/31/80

35. Flow Test Results

Flow Test Results	Flow Test Results	Flow Test Results	Flow Test Results
24	30	40	40

36. Test Interval (Top, Bottom, Used for test, tested, etc.) Sold

37. Test Witnessed by Mack C. Chase

GRN log, deviation survey

I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief.

SIGNED *Charles Chase* SECRETARY DATE 4/9/80

5.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Northwestern New Mexico

OIL OR GAS SANDS OR ZONES

IMPORTANT WATER SANDS

No. 1, from.....to.....feet.

No. 2, from.....to.....feet.

No. 3, from.....to.....feet.

No. 4, from.....to.....feet.

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation

From	To	Thickness in feet	Formation
0	35	35	Sand
35	55	20	Caliche
55	110	55	Red shale
110	130	20	Sand & gravel
130	140	10	Red shale
140	175	35	Anhydrite
175	240	65	Brown shale
240	280	40	Anhydrite
280	310	30	Shale
310	375	65	Salt
375	400	25	Anhydrite
400	500	100	Salt
500	550	50	Anhydrite
550	580	30	Salt
580	600	20	Anhydrite
600	650	50	Salt
650	900	250	Anhydrite
900	950	50	Salt
950	1250	300	Anhydrite
1250	1350	100	Lime, anhydrite
1350	1370	20	Sand
1370	1450	80	Lime, anhydrite
1450	1500	50	Lime, anhydrite, sand
1500	1510	10	Anhydrite, shale
1510	1550	40	Anhydrite
1550	1590	40	Anhydrite, sand
1590	1600	10	Anhydrite, dolomite, sand
1600	1620	20	Anhydrite, shale
1620	1720	100	Anhydrite, dolomite, sand
1720	1730	10	Anhydrite, dolomite
1730	1750	20	Anhydrite, dolomite, sand
1750	1760	10	Anhydrite, dolomite
1760	1770	10	Anhydrite, dolomite, sand
1770	1840	70	Anhydrite, dolomite
1840	1920	80	Anhydrite, dolomite, sand
1920	1940	20	Anhydrite, dolomite
1940	1950	10	Dolomite, sand
1950	1960	10	Dolomite, sand, anhydrite
1960	2000	40	Dolomite, anhydrite
2000	2040	40	Dolomite, shale, sand
2040	2200	160	Dolomite, anhydrite, sand
2200	2230	30	Dolomite, sand
2230	2300	70	Dolomite, sand, dolomite
2300	2310	10	Dolomite, sand
2310	2320	10	Dolomite
2320	2330	10	Dolomite, anhydrite, sand
2330	2360	30	Dolomite, sand
2360	2370	10	Dolomite, sand, anhydrite
2370	2380	10	Dolomite, anhydrite
2380	2400	20	Dolomite, anhydrite, sand
2400	2590	190	Dolomite, anhydrite
2590	2600	10	Dolomite, anhydrite
2600	2640	40	Dolomite, sand
2640	2670	30	Dolomite, shale
2670	2690	20	Dolomite
2690	2970	280	Dolomite, sand
2970	3000	30	Dolomite, anhydrite, sand
3000			TD
2974			PBTD