

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYForm approved.
Budget Bureau No. 42-R1424.

APR 14 1980

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)ARTESIAN OFFICE
WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th Street-Artesia, NM

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1650' FSL & 2310' FWL of Section 6-19S-25E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3630' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded a 14-3/4" hole at 5:30 PM 3-13-80.

TD 320' - Ran 8 joints of 10 3/4" 30# ST&C (322') of casing set at 320'.

1-Texas Pattern guide shoe at 320'. 1-insert float shoe at 280'. Cemented w/300 sacks of Class C 4% CaCl. PD 11:35 AM 3-14-80. Cement circulated 40 sacks to the surface. WOC 12 hours, cut off and reduced hole to 9 1/2", drilled plug and tested to 600# OK and resumed drilling.

TD 936' - Ran 23 joints of 7" 20# ST&C (940') of casing set at 936'. 1-Texas Pattern shoe at 936', insert float at 896'. Cemented w/450 sacks of 65/35 Poz, 8#/sack Kolite, 1/4#/sack celloflakes, 3% CaCl. PD 4:51 AM 3-16-80. Cement did not circulate. WOC 6 hours, ran Temperature Survey and found top of cement at 415'. Ran 1" and spotted 75 sacks of Class C 4% CaCl. PD 12:30 PM 3-16-80. WOC, ran 1" and tagged cement at 320', spotted 140 sacks of Class C 4% CaCl. PD 2:00 PM 3-16-80. WOC, ran 1" and found top of cement at 240', spotted 80 sacks of Class C 4% CaCl. Cement circulated 10 sacks to surface. PD 4:30 PM 3-16-80. WOC 18 hours, nipples up and tested to 600# OK and resumed drilling.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Geol. Secty.

DATE

4-10-80

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

APR 1980

CONDITIONS OF APPROVAL, IF ANY: