

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN T. Llicate*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-0352858-B

6. IF INDIAN, AT THE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

330' FSL & 2260' FWL of Section 6-19S-25E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3611' GR

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

Penasco Draw SA Yeso

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA (Assoc)

Sec. 6-19S-25E
Unit N. NMPM

12. COUNTY OR PARISH 13. STATE

Eddy

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded a 15" hole at 12:00 noon 3-20-80.

TD 356' - Ran 9 joints of 10-3/4" (362') of casing set at 356'. 1-guide shoe at 356', 1-insert float at 326'. Cemented w/325 sacks of Class C 4% CaCl. PD 12:00 midnight 3-20-80. Cement circulated 15 sacks of cement to the surface. Cement fell back and filled hole to surface w/4 yards of Ready-mix. WOC 12 hours. Backed off and reduced hole to 9 1/2", drilled plug and tested to 600#, OK and resumed drilling.

TD 926' - Ran 23 joints of 7" 20# K-55 (928') of casing set at 926'. 1-guide shoe at 926' and 1-insert float at 886'. Cemented w/250 sacks Howco Lite, 6#/sack gilsonite, 1/4#/sack flocele, 2% CaCl. Followed w/100 sacks Class C 2% CaCl. PD 12:00 noon 3-22-80. Circulated 30 sacks of cement to surface. WOC 18 hours, NU and tested to 1000# OK, reduced hole to 6 1/4", drilled plug and tested to 600# OK and resumed drilling.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Geol. Secty.

DATE 4-3-80

(This space for Federal or State office use)

APPROVED BY (Sgt. 882) GEORGE H. STEWART

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: