

Form 9-331
(MAY 1977 EDITION)
RECEIVEDUNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

APR 21 1980

SUDDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

ARTESIA, OFFICE

OIL WELL ☒ GAS WELL ☐ OTHER ☐**RECEIVED**

5. LEASE DESIGNATION AND SERIAL NO.

NM-0352858-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Mobil CI Federal

9. WELL NO.

6

10. FIELD AND POOL, OR WILDCAT

Penasco Draw SA Yeso (Assoc)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 6-19S-25E
Unit M NMMP

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3627' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) Spud ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Spudded a 14-3/4" hole at 8:30 PM 3-22-80.

TD 355' - Ran 9 joints of 10-3/4" 30# ST&C (359') of casing set at 355'.

1-Texas Pattern guide shoe at 355' and insert float at 315'. Cemented w/300 sacks of Class C 4% CaCl. PD 9:12 AM 3-23-80. Circulated 30 sacks of cement to the surface. WOC 12 hours. Cut off and reduced hole to 9 1/2", drilled plug and tested to 600# OK and resumed drilling.

TD 903' - Ran 21 joints of 7" 20# J-55 ST&C (904') of casing set at 903'.

1-Texas Pattern guide shoe at 903', 1-insert float at 859'. Cemented w/100 sacks of Class C Neat, 450 sacks of 65-35 Poz, 8#/sack Kolite, 1/4# /sack celloflakes, 3% CaCl. Tailed in w/150 sacks of Class C 2% CaCl. Cement circulated 20 sacks to surface. PD 4:53 AM 3-25-80. WOC 18 hours, NU and tested to 1000# OK, reduced hole to 6 1/4", drilled plug and tested to 600# OK and resumed drilling.

18. I hereby certify that the foregoing is true and correct

SIGNED

Christine Lombroso

TITLE

Geol. Secty.

DATE 4-15-80

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE