

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION **RECEIVED**
P. O. BOX 2086
SANTA FE, NEW MEXICO 87501
MAY 21 1980

Form O-103
Revised 10-1-7

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

O. C. D.
ARTESIA, OFFICE

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
B8096

SUNDY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR A WELL OR TO BE DRILLED OR TO BE DRILLED IN A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT TO PRODUCE FROM A WELL OR PROPOSED WELL)

OIL WELL ☐ GAS WELL ☒ OTHER ☐

Name of Operator

THRESHOLD DEVELOPMENT COMPANY ✓

Address of Operator

1100 Gihls Tower West, Midland, Texas 79701

Location of well

UNIT LETTER F 1980 FEET FROM THE north LINE AND 1980 FEET FROM

THE west LINE, SECTION 10 TOWNSHIP 19S RANGE 29E N.M.P.M.

11. Elevation (Show whether DF, PT, GR, etc.)

G.L. - 3379.4'

7. Unit Agreement No.

8. Prod. or Lease No. 19124

CONOCO 10-A STATE

9. Well No.

1

10. Field and Name of well

Und. Turkey Track Morrow

12. County

Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

4 FORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
WELL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☒
CASING TEST AND CEMENT JOB ☐
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☒

Description of Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work) SEE RULE 1103.

The well was spud at 6:30 p.m. on 4-3-80. A 17-1/2" hole was drilled to 435'. After attempting to run 13-3/8" O.D. casing with no success, it was decided to underream the hole to 26". The hole was opened to 26" to 150'. A large cavity formed around the rig necessitating stoppage of drilling operations. Permission was granted by Bill Gressett to plug and abandon. The well was plugged on 4-8-80 with 420 sacks; 150 sacks "C" + 2% CaCl @ 320', 270 sacks "C" + 2% CaCl @ 170', 1000 yards dirt, 8 yards ready mix filled to surface.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED David S. Pace

TITLE Exploration Manager

DATE 5/12/80

APPROVED BY B. W. Weaver

TITLE OIL AND GAS INSPECTOR

DATE MAY 10 1982

CONDITIONS OF APPROVAL, IF ANY: