

## United States Department of the Interior

RECEIVED

GEOLOGICAL SURVEY

MAR 28 1980

P. O. Drawer U
Artesia, New Mexico 88210

O. C. D.
ARTESIA, OFFICE

March 27, 1980

Cities Service Company P. O. Box 1919 Midland, Texas 79702

Gentlemen:

CITIES SERVICE COMPANY

Government AK No. 1
2130 FSL 1980 FEL Sec. 7 T.19S R.21E
Eddy County Lease No. NM 33119

Above Data Required on Well Sign

Your APPLICATION FOR PERMIT TO DRILL the above-described well to a depth of 7,110 feet to test the Morrow is hereby approved subject to compliance with the OIL AND GAS OPERATING REGULATIONS (30 CFR 221) and the following conditions:

- 1. Drilling operations authorized are subject to compliance with the attached General Requirements for Oil and Gas Operations on Federal Leases, dated July 1, 1978.
- 2. Prior to commencing construction of road, pad, or other associated developments, operator will provide the dirt contractor with a copy of the Surface Use Plan and these Conditions of Approval including the attached General Requirements.
- 3. All access roads will be limited to a 12 foot wide driving surface, excluding turnarounds. Surface disturbance associated with road construction will be limited to 20 feet in width.
- 4. Submit a Daily Report of Operations from spud date until the well is completed and the Well Completion Report (form 9-330) is filed. The report should not be less than 8" x 5" in size and each page should identify the well.
- 5. All permanent above-ground structures and equipment shall be painted in accordance with the attached Painting Guidelines. The color used should simulate Sandstone Brown (Federal Standard No. 595A, color 20318 or 30318).
- 6. Before drilling below the 8-5/8" casing, the blowout preventer assembly will consist of a minimum of one annular type and two ram type preventers.
- 7. A kelly cock will be installed and maintained in operable condition.