

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well gas well other

2. NAME OF OPERATOR
Yates Petroleum Corporation ✓

3. ADDRESS OF OPERATOR
207 So. 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 330' FSL & 330' FEL, Sec. 1-19S-24E
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input checked="" type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input checked="" type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>
(other)			

5. LEASE
NM-0439491

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME RECEIVED

8. FARM OR LEASE NAME OCT 16 1980
Federal "CW"-B

9. WELL NO. 8
O. C. D.
ARTESIA, OFFICE

10. FIELD OR WILDCAT NAME
Penasco Draw SA-Yeso Associated

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Unit P, Sec. 1-19S-24E

12. COUNTY OR PARISH Eddy 13. STATE NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3639' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 3100' - PBD 3095' WIH w/Strip gun on wireline & perforated 2826-1/2-2958' w/10 .50" holes as follows: 2826-1/2, 31, 33, 39, 55, 66, 70, 77, 2956 & 58'. Ran 97 joints of 2-3/8" tubing to 2980'. Spot acid. Treated perforations 2826-1/2-2958' w/1500 gallons 15% HCL & 30000 gallons gelled water, 45000# sand. Bled well down. WIH w/Strip gun on wireline and perforated 2692-1/2-2737' w/11 .50" holes as follows: 2692-1/2, 97-1/2, 2700, 03, 05-1/2, 09, 12, 16, 21, 24, & 37'. WIH w/2-3/8" tubing w/RBP. Set RBP at 2760'. Spot acid. Treated perforations 2692-1/2-2737' w/1500 gallons HCL, 30000 gallons gelled water, 45000# sand. Bled well down. WIH w/Strip gun on wireline and perforated 2403-2530' w/12 .50" holes as follows: 2403, 05, 08, 68, 71, 85, 99, 2501, 04, 06, 29-1/2, & 30'. Set RBP at 2566'. Spot acid. Treated perforations 2403-2530' w/30000 gallons gelled 1% KCL water, 45000# sand.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Albert K. Stall TITLE Engineer DATE Oct. 3, 1980

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

OCT 14 1980

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO