

DISTRIBUTION		
SANTA FE	1	
FILE	1	✓
U.S.G.S.		
LAND OFFICE		
OPERATOR	1	

NEW MEXICO OIL CONSERVATION COMMISSION

Supersedes Old
C-102 and C-103
Effective 1-1-65

MAY 12 1980

O. C. D.

ARTESIA, OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator

Yates Petroleum Corporation

Address of Operator

207 South 4th Street - Artesia, NM 88210

Location of Well

UNIT LETTER H . 2310' FNL FROM THE North LINE AND 330 FEET FROM

THE East LINE, SECTION 12 TOWNSHIP 19S RANGE 24E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)

3596' GR

5a. Indicate Type of Lease

State ☒ Fee ☐

5. State Oil & Gas Lease No.

L-6287

7. Unit Agreement Name

6. Farm or Lease Name Irish Hills-Yeso JE State

9. Well No.

1 3

10. Field and Pool, or Wildcat

Penasco Draw SA Yesso (Assoc)

12. County

Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

OTHER ☐

CASING TEST AND CEMENT JOB ☒

OTHER ☐

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 15" hole at 1:30 PM 4-26-80.

TD 370' - Ran 9 joints of 10-3/4" 40# J-55 ST&C casing (371') of casing set at 370'. 1-Texas pattern guide shoe at 370'. Insert float at 330'. Cemented w/350 sacks of Class C 4% CaCl. PD 1:00 AM 4-27-80. Cement circulated 35 sacks of cement to surface. WOC 12 hours, backed off, reduced hole to 9 1/2", drilled plug and tested to 600# OK and resumed drilling.

TD 933' - Ran 23 joints of 7" 20# J-55 ST&C (935') of casing set at 933'. 1-Texas pattern guide shoe at 933' and insert float at 895'. Cemented w/200 sacks of Class C Neat, 450 sacks 65-35 Poz, 8# Kolite, 1/4# celloflakes, 3% CaCl. PD 8:45 AM 4-28-80. Cement did not circulate. WOC 6 hours, ran Temperature Survey and found top of cement at 420'. Ran 1", tagged cement at 420', spotted 25 sacks Class C 4% CaCl. PD 5:00 PM 4-28-80. WOC 1 hour, ran 1" and tagged cement at 400', spotted 153 sacks Class C 3 3/4% CaCl. PD 6:30 PM 4-28-80. Cement circulated 10 sacks to surface. WOC 18 hours, NU and tested to 1000# OK, reduced hole to 6 1/4", drilled plug and tested to 600# OK and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Tomlinson TITLE Geol. Secty.

DATE 5-10-80

APPROVED BY W.A. Gussitt

TITLE SUPERVISOR, DISTRICT II

DATE MAY 13 1980

CONDITIONS OF APPROVAL, IF ANY:



BENNETT WIRE LINE SERVICE

P. O. BOX 787
ARTESIA, NEW MEXICO 88210
Phone 746-3281



DANNY JACKSON

TEMPERATURE SURVEY

RECEIVED

OPERATOR YATES PETROLEUM CORP MAY 12 1980

LEASE IRISH HILLS "JE"

WELL NO. #3 O. C. D.

FIELD NO. ARTESIA, OFFICE

DATE & TIME CEMENT JOB COMPLETED 4-28-80 0830 HOURS

DATE & TIME SURVEY MADE 4-28-80 1400 HOURS

SURVEY RUN BY B.J. CATHEY

DATUM

WELL DATA TOTAL DEPTH 835 FEET

CEMENT TOP 425 FEET

