

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. L-6287	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

RECEIVED

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>		7. Unit Agreement Name	
2. Name of Operator Yates Petroleum Corporation		8. Farm or Lease Name Irish Hills-Yeso JE State	
3. Address of Operator 207 South 4th Street-Artesia, NM 88210		9. Well No. 3	
4. Location of Well UNIT LETTER H 2310 FEET FROM THE North LINE AND 330 FEET FROM THE East LINE, SECTION 12 TOWNSHIP 19S RANGE 24E NMPM.		10. Field and Pool, or Wildcat Penasco Draw SA Yeso (Assoc)	
15. Elevation (Show whether DF, RT, GR, etc.) 3596' GR		12. County Eddy	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER Set Prod. csg, perf, & treat <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 3101' - Ran 74 joints of 4½" 9.5# J-55 (3101') of casing set at 3101'. 1-Diff-fill shoe at 3101'. 6-centralizers. Cemented w/350 sacks 50-50 Poz w/2/10% D-65, 3/10% D-108 - 3# D-44. PD 1:52 PM 5-8-80. Cement circulated 61 sacks of cement to the surface. WOC and tested to 1000# OK.  
TD 3101' - WIH w/Steel Strip gun and perforated 2576-2595' w/10 .50" holes (1-shot at each depth) as follows: 2576, 78, 80, 82, 84, 86, 88, 90, 92, & 95'. Sand Frac'd perforations w/25280 gallons of treated gelled water, 75000# sand - 15000# 100 mesh and 60000# 20-40 sand. Installed pumping equipment.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Imbuson TITLE Geol. Secty. DATE 6-10-80

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE JUN 12 1980

CONDITIONS OF APPROVAL, IF ANY: