

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.O.S.	
LAND OFFICE	
OPERATOR	1

RECEIVED  
OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87101  
MAY 22 1980

Form C-103  
Revised 10-1-78

O. C. D.  
ARTESIA, OFFICE

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. L-6287

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- 2. Name of Operator Yates Petroleum Corporation ✓ 3. Address of Operator 207 South 4th Street-Artesia, NM 88210 4. Location of Well UNIT LETTER G 2310' FEET FROM THE North LINE AND 1650 FEET FROM East 12 TOWNSHIP 19S RANGE 24E NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 3591' GR	7. Unit Agreement Name 8. Farm or Lease Name Irish Hills-Yeso JE 9. Well No. State 5 10. Field and Pool, or Wildcat Penasco Draw SA Yeso (Assoc) 12. County Eddy
---	---

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 15" hole at 4:30 PM 5-16-80.

TD 370' - Ran 10 joints of 10-3/4" 40.5# K-55 (396') of casing set at 370'. 1-Texas Pattern guide shoe at 370' and insert float at 330'. Cemented w/375 sacks of Class C 4% CaCl. PD 10:00 AM 5-17-80. WOC. Cement fell back and filled hole to surface w/5 yards of Ready-Mix. WOC 12 hours, cut off, reduced hole to 9 1/2", drilled plug and tested to 600# OK and resumed drilling.  
TD 925' - Ran 21 joints of 7" 20# K-55 ST&C (927') of casing set at 925'. 1-Regular Pattern guide shoe at 925' and insert float at 885'. Cemented w/250 sacks of Class C neat, 450 sacks 65-35 Poz, w/8# Kolite, 1/4# celloflakes 3% CaCl. Tailed in w/150 sacks Class C, 2% CaCl. PD 1:00 PM 5-18-80. Cement did not circulate. WOC 4 1/2 hrs, ran Temperature Survey found top of cement at 385'. Ran 1", tagged cement at 385', spotted 25 sacks Class C 4% CaCl. WOC 2 hrs, ran 1" and tagged cement at 294', spotted 110 sacks Class C 4% CaCl. Circulated 10 sacks to surface. PD 8:30 PM 5-18-80. WOC 18 hours, NU, reduced hole to 6 1/4", drilled plug and tested to 600# OK and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christie L. Linder TITLE Geol. Secty. DATE 5-21-80

APPROVED BY W.A. Gussert TITLE SUPERVISOR, DISTRICT II DATE MAY 23 1980

CONDITIONS OF APPROVAL, IF ANY: