

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐ OCT 20 1980
2. NAME OF OPERATOR Yates Petroleum Corporation
3. ADDRESS OF OPERATOR 207 So. 4th St., Artesia, NM 88210
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 400' FSL & 990' FWL
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input checked="" type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) <input type="checkbox"/>	<input type="checkbox"/>

5. LEASE NM 439491
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME Federal CW-B
9. WELL NO. 5
10. FIELD OR WILDCAT NAME Penasco Draw SA-Yeso Associated
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Unit M-Sec. 1-19S-24E
12. COUNTY OR PARISH Eddy 13. STATE NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD) 3679' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded a 15" hole at 4:30 PM 10-10-80
TD 380' Ran 9 joints of 10-3/4" 32.75# ST&C H-40 casing set at 380'. 1-Notched guide shoe at 380'. Flapper insert at 338'. Cemented w/375 sacks Class "C" 4% CaCl. PD 3:45 AM 10-11-80. Cement circulated 40 sacks. WOC 12 hours. Reduced hole to 9-1/2". Drilled plug and tested to 600#, OK. Resumed drilling.
TD 916' Ran 21 joints of 7" 20# J-55 ST&C casing set at 915'. 1-Texas Pattern guide shoe at 915'. Flapper insert at 870'. Cemented w/400 sacks 65-35, 4% Bentonite, 8# Kolite, 1/4# cellofalke and 3% CaCl. Tailed in w/150 sacks Class "C" 2% CaCl. PD 10:45 AM 10-12-80. Cement circulated 50 sacks. WOC 18 hours. Nippled up and tested to 1500#, OK. Reduced hole to 6-1/4". Drilled plug and tested to 600#, OK. Resumed drilling.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Albert L. Hall TITLE Engineer DATE October 13, 1980

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:
ACCEPTED FOR RECORD
OCT 15 1980
U.S. GEOLOGICAL SURVEY

TITLE _____ DATE _____
RECEIVED
OCT 15 1980
*See Instructions on Reverse Side
U.S. GEOLOGICAL SURVEY