

N.M.O.C.D. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN THE
(Other instructions on re-
verse side)Form approved:
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

NM-0439491

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal CW-B

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

Penasco Draw SA Yeso Assoc.

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREAUnit M-
Sec. 1-19S-24E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different formation.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐
NOV 18 1980

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

400' FSL & 990' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3679' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Prod. casing, perforate, trt X

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 3100' Ran 77 joints of 4-1/2" 9.5# J-55 casing set at 3089'. Diff-fill shoe at 3089'.
Used 6 centralizers. Cemented w/350 sacks 50-50 Poz, .75% CF-2, 2% KCL and .2% AF-11.
PD 4:25 PM 10-22-80. Cement circulated 40 sacks to pit. WOC and tested to 1500 psi, OK.
TD 3100'; PBTD 3089' WIH w/Steel Strip gun on wireline and perforated 2507-1/2-2908' w/15
.50" holes as follows: 2507-1/2, 12, 14-1/2, 17, 19, 64, 66, 87, 89, 2667, 80, 82, 2904,
06, & 08'. Frac'd w/60000 gallons gelled 1% KCL water, 90000# sand (10000# 100 mesh &
80000# 20-40 sand).

RECEIVED
NOV 14 1980U. S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Engineer

DATE Nov. 12, 1980

(This space for Federal or State office use)

APPROVED BY PETER W. CHESTER
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

NOV 14 1980

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side