

Form 9-331
Dec. 1973Form Approved.
Budget Bureau No. 42-R1424UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
well well

2. NAME OF OPERATOR
Yates Petroleum Corporation ✓

3. ADDRESS OF OPERATOR
207 So. 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1700' FSL & 330' FEL
AT SURFACE:
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input checked="" type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) <input type="checkbox"/>	<input type="checkbox"/>

5. LEASE
NM 0439491

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Federal CW-B

9. WELL NO.

7

10. FIELD OR WILDCAT NAME

Penasco Draw SA Yeso Associated

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unit I, Sec. 1-19S-24E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3653.4' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330)

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 424' Spudded at 15" hole at 1:30 PM 9-30-80. Ran 10 joints of 10-3/4" 40.50# K-55 ST&C casing set at 424'. 1 shoe joint at 424'. Flapper float at 389'. Cemented w/400 sacks Class C 4% CaCl. PD 5:00 AM 10-1-80. Cement circulated 35 sacks. WOC 12 hours. Reduced hole to 12-1/4". Drilled plug & tested to 600#, OK. Resumed drilling.

TD 947' Ran 22 joints of 7" 20# K-55 casing set at 947'. 1-Texas Pattern guide shoe at 947'. Flapper float at 907'. Cemented w/200 sacks Class C Neat, 800 Sacks 65-35 Poz, 4% Bentonite, 8# celloflake & 3% CaCl. Tailed in w/150 sacks Class C 2% CaCl. PD 5:00 PM 10-2-80. Cement did not circulate. WOC 6 hours. Ran Temperature Survey & found top of cement at 390'. Ran 1". Tagged cement at 390'. Spotted 25 sacks Class C 4% CaCl. PD 11:30 PM 10-2-80. Ran 1". Tagged cement at 390'. Spotted 200 sacks Class C 4% CaCl. PD 1:45 AM 10-3-80. Circulated 10 sacks to pit. WOC 18 hours. Nippled up & tested to 1500#, OK. Reduced hole to 6-1/4". Drilled plug & tested to 600#, OK. Resumed drilling.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Albert R. Hall TITLE Engineer DATE 10-8-80

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

OCT 14 1980

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO