

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN THE ICATE*
(Other instruct. on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-0352858-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

APR 28 1980

7. UNIT AGREEMENT NAME

ARTESIA OFFICE

8. FARM OR LEASE NAME

Mobil CI Federal

9. WELL NO.

7

10. FIELD AND POOL, OR WILDCAT

Penasco Draw SA Yeso (Assoc)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREASec. 6-19S-25E
Unit J NMPM

12. COUNTY OR PARISH 13. STATE

Eddy NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, NM 88210 NEW MEXICO

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1650' FSL & 1650' FEL of Section 6-19S-25E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3612' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Set Production casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 3100' - Rigged up Pool Well Service Unit. Ran 70 joints of 4½" 9.5# J-55 (3076') of casing set at 3076'. 1-Guide Shoe at 3076'. Cemented w/350 sacks Class C 3/10% D-108, 2/10% D-65. PD 5:30 PM 4-14-80. Cement circulated 30 sacks to surface.

TD 3100'; PBTD 3076'. WIH w/Strip Gun on wireline and perforated 2278'-2963'w/26 .50" holes (1 shot at each depth) as follows: 2278, 85, 90, 2400, 03, 08, 2508, 21, 23, 96, 99, 2602, 05, 07, 10, 12, 84, 87, 2705½, 10, 13, 2927, 29, 35, 60, & 63'. (Total 26 holes). Broke down formation w/2000 gallons of 15% acid. Sand Frac'd perforations w/65100 gallons gelled 1% KCL water, 95000# sand, 20000# 100 mesh and 75000# 20-40 sand. Installed pumping equipment and recovering load.

18. I hereby certify that the foregoing is true and correct

SIGNED

Christine Lombard

TITLE

Geol. Secty.

DATE

4-24-80

(This space for Federal or State office use)

GEORGE D. STEWART

APPROVED BY

TITLE

GEORGE D. STEWART

DATE

4-24-80

CONDITIONS OF APPROVAL, IF ANY: