

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.
NM-0352858

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
MAY - 5 1980

7. UNIT AGREEMENT NAME
O.C.D.

8. FARM OR LEASE NAME
ARTESIA, OFFICE

Mobil CI Federal

9. WELL NO.
8

10. FIELD AND POOL, OR WILDCAT
Penasco Draw SA Yeso (Assec)

11. SEC. T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 6-19S-25E
Unit I NMPM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3612' GR

12. COUNTY OR PARISH
Eddy

13. STATE
NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Spudded a 15" hole at 8:00 PM 3-29-80.

TD 359' - Ran 9 joints of 10-3/4" 32.75# H-40 (362') of casing set at 359'. 1-guide shoe at 359' and insert float at 319'. Cemented w/250 sacks Class C 4% CaCl. PD 7:00 AM 3-30-80. Circulated 25 sacks of cement to the surface. WOC 12 hours, reduced hole and backed off, drilled plug and tested to 600# OK and resumed drilling.

TD 936' - Ran 26 joints of 7" 20# J-55 (938') of casing set at 936'. Cemented by Howco w/400 sacks Howco-Lite Class H, 5#/sack gilsonite, 1/4#/sack flocele, 2% CaCl. Followed w/100 sacks Class C 2% CaCl. PD 11:45 PM 3-31-80. Circulated 10 sacks of cement to surface. WOC and cement fell back, filled hole w/4 yards of Ready-Mix. WOC 18 hours, NU and tested to 1000# OK, reduced hole to 6 1/4", drilled plug and tested to 600# OK and resumed drilling.

RECEIVED

APR 28 1980

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Christine Tomblinson

TITLE Geol. Secty.

DATE 4-26-80

(This space for Federal or State office use)

ACTING DISTRICT ENGINEER

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: