

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

MAY 12 1980

O. C. D.

ARTESIA, OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER-	5a. Indicate Type of Lease State ☒ Fee ☐
2. Name of Operator Yates Petroleum Corporation	5. State Oil & Gas Lease No. OG 783
3. Address of Operator 207 South 4th Street - Artesia, NM 88210	7. Unit Agreement Name
4. Location of Well UNIT LETTER E 2310 FEET FROM THE North LINE AND 990 FEET FROM THE West LINE, SECTION 5 TOWNSHIP 19S RANGE 25E NMPM	8. Farm or Lease Name Greasewood BD State
	9. Well No. 1 8
	10. Field and Pool or Lease Unit Penasco Draw SA Yeso (Assoc.)
15. Elevation (Show whether DF, RT, GR, etc.) 3603' GR	12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
-------------------------	-----------------------

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☒	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☒	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 14-3/4" hole at 4:00 PM 4-25-80.

TD 360' - Ran 9 joints of 10-3/4" 32# J-55 (372') of casing set at 360'. 1-Texas Pattern guide shoe at 360'. Insert float at 320'. Cemented w/360 sacks of Class C 4% CaCl. PD 8:45 AM 4-26-80. Cement circulated 30 sacks to surface. WOC 12 hours. Cut off, reduced hole to 9 1/2", drilled plug, tested to 600# OK and resumed drilling.

TD 949' Ran 24 joints of 7" 20# K-55 ST&C (965') of casing set at 949'. 1-Guide shoe at 949', insert float at 908'. Cemented w/250 sacks of Class C 3% CaCl, 450 sacks 65-35 Poz, 1/4# celloflakes, 10# Kolite, 3% CaCl. Tailed in w/150 sacks Class C 2% CaCl. PD 11:30 PM 4-27-80. Cement did not circulate. WOC 6 hours, ran Temperature Survey and found top of cement at 479'. Ran 1" and tagged cement at 465', spotted 150 sacks Class C 4% CaCl. PD 6:30 AM 4-28-80. Circulated 5 sacks to surface. WOC 18 hours, NU and tested to 1000# OK, reduced hole to 6 1/4", drilled plug and tested to 600# OK and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Justin Tomlinson TITLE Geol. Secty. DATE 5-10-80

APPROVED BY W.A. Gressett TITLE SUPERVISOR, DISTRICT II DATE MAY 13 1980

CONDITIONS OF APPROVAL, IF ANY:



BENNETT WIRE LINE SERVICE

P. O. BOX 787
ARTESIA, NEW MEXICO 88210
Phone 746-3281



MR. JONAS

TEMPERATURE SURVEY RECEIVED

OPERATOR YATES PETROLEUM CORP

LEASE GRASE WOOD "BD"

MAY 12 1980

WELL NO. #8

O. C. D.

FIELD NO. _____

ARTESIA, OFFICE

DATE & TIME CEMENT JOB COMPLETED 4-27-80 2225 HOURS

DATE & TIME SURVEY MADE 4-28-80 0400 HOURS

SURVEY RUN BY B.J. CATHEY

DATUM _____

WELL DATA TOTAL DEPTH 912 FEET

CEMENT TOP 430 FEET

