

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

RECEIVED

Form C-103
Revised 10-1-78

MAY - 9 1980

O. C. D.

SUNDRY NOTICES AND REPORTS ON WELLS ARTESIA, OFFICE

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
2. Name of Operator Amoco Production Company	5. State Oil & Gas Lease No.
3. Address of Operator P. O. Box 68 Hobbs, NM 88240	7. Unit Agreement Name
4. Location of Well UNIT LETTER <u>E</u> <u>2080</u> FEET FROM THE <u>North</u> LINE AND <u>860</u> FEET FROM THE <u>West</u> LINE, SECTION <u>1</u> TOWNSHIP <u>19-S</u> RANGE <u>25-E</u> NMPM.	8. Farm or Lease Name Alley
	9. Well No. 1
	10. Field and Pool, or Wildcat Und. Morrow
15. Elevation (Show whether DF, RT, GR, etc.) 3463.5 GL	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	
		OTHER <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

On 4-25-80 Sharp Drilling Co. (Rig #62) spudded a 17-1/2" hole at 4:00 p.m. Drilled to a TD of 400' and ran 13-3/8" 48# H-40 ST&C casing set at 400'. Cemented with 450 SX Class C cement with 2% CACL. Plugged down at 10:45 a.m. 4-26-80. Circulated 65 SX. WOC 19 hours. Tested casing with 600# for 30 min. Test OK. Reduced hole to 12-1/4" and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Bob Davis TITLE Admin. Analyst DATE 5-6-80

APPROVED BY W.A. Gussert TITLE SUPERVISOR, DISTRICT II DATE MAY - 9 1980

CONDITIONS OF APPROVAL, IF ANY:

0-1 MNOCH A 1-Hobbs 1-Suen 1-LRD 1-Anadarko 1-Champlin 1-Charles H. Coll