

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE	1	
FILE	1	✓
U.S.O.S.		
LAND OFFICE		
OPERATOR	1	

JUN 16 1980

O. C. D.  
ARTESIA, OFFICE

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Amoco Production Company ✓		8. Farm or Lease Name Alley
3. Address of Operator P. O. Box 68 Hobbs, NM 88240		9. Well No. 1
4. Location of Well UNIT LETTER <u>E</u> , <u>2080</u> FEET FROM THE <u>North</u> LINE AND <u>860</u> FEET FROM THE <u>West</u> LINE, SECTION <u>1</u> TOWNSHIP <u>19-S</u> RANGE <u>25-E</u> NMPM.		10. Field and Pool, or Wildcat Und. Morrow
15. Elevation (Show whether DF, RT, GR, etc.) 3463.5 GL		12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:      SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled to a TD of 9362' and ran 603' 5-1/2" 17#, N-80 and 8357' 5-1/2" 15.5# K-55 and 402' 5-1/2" 17# K-55 set at 9362'. Cemented with 1750 SX Haliburton Lite cement with 1/4# Flocele and 250 SX Class H cement. Plugged down 5:25 a.m. 5-29-80. Top of cement found by temp survey at approx. 1140'. Will test casing when move in completion unit.

0+4-NMOCD,A      1-Hou      1-Susp      1-BD      1-Anadarko      1-Champlin      1-Charles Coll

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Bob Davis TITLE Admin. Analyst DATE 6-11-80

APPROVED BY W. A. Gressitt TITLE SUPERVISOR, DISTRICT II DATE JUN 17 1980

CONDITIONS OF APPROVAL, IF ANY: