

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates Petr Corp</u>		Lease <u>Greasewood B D State</u>		Well # <u>9</u>	
Location of Well	Unit <u>D</u>	Section <u>5</u>	Township <u>19</u>	Range <u>2S</u>	County <u>Eddy</u>
Drilling Contractor	<u>Cactus</u>		Type of Equipment <u>Rotary</u>		

* Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
15"	10 3/4	32.75#		350'	Circ
* 9 5/8	7	20#		985'	Circ
6 1/4	4 1/4	9.5#		3150'	Circ

Casing Data:

Surface _____ joints of 7" inch 20 # Grade J-SS
(Approved) (Rejected) _____

Inspected by _____ date _____

Cementing Program

Size of hole 9 1/2" Size of Casing 7" Sacks cement required _____

Type of Shoe used guide Float collar used Insert Btm 3 jts welded yes

TD of hole 963' Set 962' Feet of 7 Inch 20 # Grade J-SS

(New-used csg. @ 962' with 150 sacks neat cement around shoe

+ 350 sack 65/35 per cent additives (8# Kolite, 1/4# alfolakes, 4% D²⁰ gel, 3% ca)

Plug down @ 1:00 (AM) (PM) Date 5/13/80

Cement circulated yes No. of Sacks 30

Cemented by Dowell Witnessed by Mike Shillfield

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____

Full returns to TD

No centralizers

last daily break @ 859'