

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

RECEIVED

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

JUN 5 1980

O. C. D.

ARTESIA, OFFICE

5a. Indicate Type of Lease

State ☒ Fee ☐

5. State Oil & Gas Lease No.
OG-783

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- 2. Name of Operator Yates Petroleum Corporation ✓ 3. Address of Operator 207 South 4th Street - Artesia, NM 88210 4. Location of Well UNIT LETTER D 990 FEET FROM THE North LINE AND 990 FEET FROM West LINE, SECTION 5 TOWNSHIP 19S RANGE 25E NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 3606' GR	7. Unit Agreement Name 8. Farm or Lease Name Greasewood BD State 9. Well No. 9 10. Field and Pool, or Wildcat Penasco Draw SA-Yeso (Assoc) 12. County Eddy
--	--

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☒
CASING TEST AND CEMENT JOBS ☒
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 14-3/4" hole at 9:00 AM 5-11-80.

TD 377'- Ran 10 joints of 10-3/4" 30# K-55 ST&C (384') of casing set at 377'. 1-Texas Pattern Guide shoe at 377', flapper float at 337'. Cemented w/350 sacks Class C 4% CaCl. PD 2:00 PM 5-11-80. Circulated 30 sacks to surface. WOC 12 hours, cut off, reduced hole to 9 1/2", drilled plug, tested to 600# and resumed drilling.

TD 963'- Ran 24 joints of 7" 20# K-55 (965') of casing set at 963'. 1-Texas Pattern Guide Shoe at 963' and insert float at 923'. Cemented w/350 sacks of 65-35 Poz, 3# Kolite, 4/10% Bentonite, 1/4#/sack celloflakes, 3% CaCl. Tailed in w/150 sacks Class C 2% CaCl. Circulated 30 sacks of cement to the surface. PD 1:00 AM 5-13-80. WOC 18 hours, NU, reduced hole to 6 1/4", drilled plug, tested to 600# OK and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Imburson

TITLE Geol. Secty

DATE 6-4-80

APPROVED BY W.A. Gussitt

TITLE SUPERVISOR, DISTRICT II

DATE

JUN 5 1980

CONDITIONS OF APPROVAL, IF ANY: