

N.M.O.C.D. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRI
(Other instructi
verse side)CATE*
on re-Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-29607

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

BUZZARD FEDERAL Com.

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

WILDCAT Morgan

11. SEC., T., R., M., OR BLK. AND

SURVEY OR AREA
SEC 17, T20S, R23E

12. COUNTY OR PARISH

EDDY

13. STATE

NEW MEXICO

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> DRY HOLE
2. NAME OF OPERATOR MESA PETROLEUM CO
3. ADDRESS OF OPERATOR 1000 VAUGHN BUILDING/MIDLAND, TEXAS 79701
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FWL & 2310' FSL
14. PERMIT NO.
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4252.7' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Received verbal approval to P&A from George Stewart, USGS, Artesia at 10:10 AM 6-15-80. Set 45 sxs Class "H" at 8607'-8507', 8261'-8161', and 7759'-7659'. Set 50 sxs Class "H" at 6755'-6655' and at 6096'-5996'. Set 70 sxs "H" + 2% CaCl at 3710'-3610'. Set 50 sxs "H" + 2% CaCl at 1858'-1758'. Set 35 sxs "H" + 2% CaCl at 351'-251'. Set surface plug with 25 sxs "H" + 2% CaCl from 69' to surface. Well P&A 7:30 AM 6-16-80. Rig released at 3 PM 6-16-80.

Form 9-330 will be submitted when logs are received.

18. I hereby certify that the foregoing is true and correct

SIGNED

R. E. Stewart

TITLE

Regulatory Coordinator

DATE 6-18-80

(This space for Federal or State office use)

APPROVED BY *(Orig. Sgd.)* GEORGE H. STEWART

TITLE

ACTING DISTRICT ENGINEER

DATE

JUN 20 1980

CONDITIONS OF APPROVAL, IF ANY:

XC: USGS (6), TLS, JBH, JWH, MEC, CENTRAL RCDS, ACCTG, PARTNERS, FILE,

*See Instructions on Reverse Side