

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE\*  
(Other instructions on re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-36500

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Cotton MX Federal Com

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Und. Boyd Morrow

11. SEC., T., R., M., OR BLK. AND

Sec. 14-19S-25E

Unit C NMPM

12. COUNTY OR PARISH 13. STATE

Eddy

NM

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Yates Petroleum Corporation ✓

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, NM

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

810' FNL &amp; 2180' FWL of Section 14-19S-25E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3430' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) \*

Spudded a 17½" hole at 3:00 PM 5-16-80.

TD 416'- Ran 10 joints of 13-3/8" 54# H-40 ST&C (418') of casing set at 416'. 1-Texas Pattern Guide shoe at 416' and insert float at 376'. Cemented w/400 sacks Class C 4% CaCl. Slurry wt. 14.8, 1.32 cu ft/sx. Compressive Strength at 70 degrees 1023 psi in 12 hours. PD 10:45 PM 4-17-80. WOC 12 hours. Cut off, reduced hole to 12½", drilled plug, tested to 600# OK and resumed drilling.

TD 1230' - Ran 31 joints of 8-5/8" 24# J-55 ST&C (1235') of casing set at 1230'. 1-Guide Shoe at 1230' and insert float at 1190'. Cemented w/550 sacks Howco Lite, 5#/sack gilsonite, 1/4#/sx flocele, 2% CaCl. Tailed in w/150 sacks Class C 2% CaCl. PD 1:00 AM 5-20-80. Circulated 150 sacks of cement to surface. WOC 18 hours, NU, tested to 1500# OK and reduced hole to 7-7/8", drilled plug, tested to 600# OK and resumed drilling.

RECEIVED

MAY 28 1980

O. C. D.  
ARTESIA, OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED

*Christine J. J. J.*

TITLE

Geol. Secty.

DATE

5-21-80

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: