NMC

Form 9-331 (May 1963)

UNITED STATES SUBMIT IN TRIPLICATE (Other Instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION (APP VIRIAL NO.

NM-0554472 GEOLOGICAL SURVEY 6. IF INDIAN, ALLOTTEE OR TRIBE NAME SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT" for such proposals.) 7. UNIT AGREEMENT NAME 才 1. 日本 1分科C管 WELL X OTHER 8. FARM OR LEASE NAME Irish Hills-Yeso NM 2. NAME OF OPERATOR Yates Petroleum Corporation Federal 9. WELL NO. 3. ADDRESS OF OPERATOR 1 207 South 4th Street - Artesia, NM 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) 10. FIELD AND POOL, OR WILDCAT Penasco Draw SA Yeso (Assoc.) At surface 11. SEC., T., R., M., OR BLK. AND 990' FNL & 2310' FWL of Section 12-198-24E Serit12-195m24E 12. COUNTY OR PARISH | 13. STATE 15. ELEVATIONS (Show whether DF, RT, GR. etc.) 14. PERMIT NO. Eddy

		3017	3K	1 150	<u> </u>	TATAL
16.	Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data					
	NOTICE OF INTENTION TO:			SUBSEQUENT REPORT OF:		
TEST WATE FRACTURE 1 SHOOT OR A REPAIR WEI	CIDIZE	PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON* CHANGE PLANS	WATER SHUT-OFF FRACTURE TREATM SHOOTING OR ACID (Other) (NOTE: Rep	DIZING X	REPAIRING WELL ALTERING CASING ABANDONMENT*	,

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 3100'; PBTD 3094' - Moved in and rigged up completion unit. WIH w/Steel Strip gun on wireline and perforated 2442-2547 w/18 .50" holes (1 shot at each depth) as follows: 2538-47' w/10 .50" holes. 2538, 39, 40, 41, 42, 43, 44, 45, 46 and 47'. POH. Sand Frac'd perforations w/1500 gallons 15% acid, 20000 gallons gelled 1% KCL, 40000# sand (5000# 100 mesh and 35000# 20-40 sand). Bled well down. WBIH w/Steel Strip gun on wireline and perforated 2442-49' w/8 .50" holes as follows: 2442, 43, 44, 45, 46, 47, 48 and 49'. POH. WIH w/RBP set at 2449' and Sand Frac'd perforations w/1500 gallons 15% acid, 20000 gallons gelled 1% KCL water and 40000# sand (5000# 100 mesh, 35000# 20-40 sand). Pulled RBP and installed pumping equipment.

ACCEPTED FOR RECORD

AUG 131980

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true a	md correct Median DITLE Geol. Secty.	DATE 8-6-80
(This space for Federal or State office use)		
APPROVED BY	TITLE	DATE