

N.M.O.C.D. COPY

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-0352858-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Mobil CI Federal

9. WELL NO.

10

10. FIELD AND POOL, OR WILDCAT

Penasco Draw SA Veso
(Assoc.)11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREASec. 5-19S-25E
Unit L NMPM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

ARTESIA, OFFICE

3595' GR

12. COUNTY OR PARISH

Eddy

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☒
☒
☒
☐

REPAIRING WELL

☐
☐
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 3029'; PBD 3005' - WIH w/Steel Strip gun on wireline and perforated 2505-2631' w/18 .50" holes as follows: 2619-31' w/10 .50" holes as follows: 2619, 21, 23, 24, 25, 26, 27, 28, 29 and 31' (1 shot at each depth). Ran tubing to 2630' and spotted 1500 gallons 15% acid. Sand Frac'd w/20000 gallons gelled 1% KCL water, 40000# sand (5000# 100 mesh and 35000# 20-40 sand. POH. WIH w/Steel gun on wireline and perforated 2504-11' w/8.50" holes as follows: 2504, 05, 06, 07, 08, 09, 10 and 11'. POOH. WIH and set RBP at 2480' w/900# pressure. Sand Frac'd w/1500 gallons acid, 15000 gallons gelled 1% KCL water, 30000# sand, 5000# 100 mesh and 25000# 20-40 sand. Pulled RBP and installed pumping equipment.

ACCEPTED FOR RECORD

AUG 13 1980

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Christine Tomlinson

TITLE

Geol. Secty.

DATE

8-5-80

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: