

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR  
Amoco Production Company

3. ADDRESS OF OPERATOR  
P. O. Box 68 Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980' FSL & 860' FWL, Sec. 26  
AT TOP PROD. INTERVAL: (Unit L, NW/4, SW/4)  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

RECEIVED

SEP 18 1980

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

5. LEASE  
LC-029392-B  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
Greenwood PreGrayburg Unit  
8. FARM OR LEASE NAME  
Greenwood PreGrayburg Unit Federal F Com.  
9. WELL NO.  
10. FIELD OR WILDCAT NAME  
Wildcat Ellenburger  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
26-18-31  
12. COUNTY OR PARISH  
Eddy  
13. STATE  
NM  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3651.8 GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

On 8-30-80, Kenai Big West Drilling Co. (rig #22) spudded a 20" hole at 5:00 p.m. Drilled to a TD of 800' and ran 65# H-40 16" casing set at 800'. Cemented with 900 SX Incor cement with 2% CACL. Circulated 100 SX. WOC 18 hr. Tested casing with 1000# for 30 min. Test OK. Reduced hole to 14-3/4" and resumed drilling.

0+5-USGS, H 1-Hou 1-Susp 1-LBG 1-W. Stafford, Hou

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Benton Green TITLE Ast. Adm. Analyst DATE 9-17-80

APPROVED BY D. Chester TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

SEP 22 1980

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

RECEIVED

SEP 24 1980

O. C. D.

ARTESIA, OFFICE