		00PY TO 0. 6	Form Approved.
Dec. 1973	UNITED STATE	s	Budget Bureau No. 42–R1424
	PARTMENT OF THE		5. LEASE LC-029392-B
	GEOLOGICAL SUR		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NO	OTICES AND REP	ORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form f reservoir. Use Form 9-3	for proposals to drill or to de 331–C for such proposals.)	epen or plug back to a differ	rent Greenwood Pregrayburg Unit
1. oil ga well we	as ell 💭 other		Greenwood Pregrayburg Unit FED F CON 9. WELL NO.
2. NAME OF OPE			10. FIELD OR WILDCAT NAME
AMOCO Prod 3. ADDRESS OF (duction Company	V	Wildcat Ellenburger
P. 0. Box		M 88240	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF	WELL (REPORT LOCATIO		
below.) AT SURFACE:	1980' ESL X 80	50' FWL, Sec. 26	26-18-31 12 COUNTY OR PARISUL 12 CTATE
	. INTERVAL: (Unit L	, NW/4, SW/4)	12. COUNTY OR PARISH 13. STATE
AT TOTAL DEP	TH:		14. API NO.
16. CHECK APPRO REPORT, OR C	PRIATE BOX TO INDIC.	ATE NATURE OF NOTIO	
on t			15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APP		SEQUENT REPORT OF	
TEST WATER SHUT			RECEIVE AND RECEIVE
SHOOT OR ACIDIZ	E		
REPAIR WELL PULL OR ALTER C			(NOTE) Report results of multiple completion or zone change on Form 9–330.)
MULTIPLE COMPLE		📋 U.S.	(10)
CHANGE ZONES ABANDON*		он Ц	BBS, NEW MEXICO
(other)			ARTESIA, OF
17. DESCRIBE PRO	OPOSED OR COMPLETED	OPERATIONS (Clearly	state all pertinent details, and give pertinent dates,
including estim			
measured and	nated date of starting an	v proposed work. If well	is directionally drilled, give subsurface locations and
measured and	nated date of starting an true vertical depths for a	v proposed work. If well	is directionally drilled, give subsurface locations and
measured and	nated date of starting an true vertical depths for a	y proposed work. If well Il markers and zones pert	is directionally drilled, give subsurface locations and tinent to this work.)*
measured and Drilled to	nated date of starting an true vertical depths for a o a TD of 4797' a	y proposed work. If well Il markers and zones perf and ran 1295' of	is directionally drilled, give subsurface locations and tinent to this work.)*
measured and Drilled to 45.5# K-55	nated date of starting an true vertical depths for a o a TD of 4797' a 5 10-3/4" casing	y proposed work. If well Il markers and zones perf and ran 1295' of and 2643' of 40.	is directionally drilled, give subsurface locations and tinent to this work.)* 51# K-55 10-3/4" casing, 1098' of .5# K-55 10-3/4" casing set at
measured and Drilled to 45.5# K-55 4797' ceme C Neat cer	nated date of starting an true vertical depths for a o a TD of 4797' a 5 10-3/4" casing ented with 3400 s ment. Plugged do	y proposed work. If well I markers and zones perf and ran 1295' of and 2643' of 40. SX Lite cement wi own at 9:30 a.m.	is directionally drilled, give subsurface locations and tinent to this work.)* 51# K-55 10-3/4" casing, 1098' of 5# K-55 10-3/4" casing set at ith additives and 200 SX Class 9-16-80. Circulated 257 SX.
measured and Drilled to 45.5# K-55 4797' ceme C Neat cer WOC 18 hr.	nated date of starting an true vertical depths for a 5 10-3/4" casing ented with 3400 S ment. Plugged do . Tested casing	y proposed work. If well I markers and zones perf and ran 1295' of and 2643' of 40. SX Lite cement wi own at 9:30 a.m. with 2000# for 3	is directionally drilled, give subsurface locations and tinent to this work.)* 51# K-55 10-3/4" casing, 1098' of .5# K-55 10-3/4" casing set at ith additives and 200 SX Class
measured and Drilled to 45.5# K-55 4797' ceme C Neat cer WOC 18 hr.	nated date of starting an true vertical depths for a o a TD of 4797' a 5 10-3/4" casing ented with 3400 s ment. Plugged do	y proposed work. If well I markers and zones perf and ran 1295' of and 2643' of 40. SX Lite cement wi own at 9:30 a.m. with 2000# for 3	is directionally drilled, give subsurface locations and tinent to this work.)* 51# K-55 10-3/4" casing, 1098' of 5# K-55 10-3/4" casing set at ith additives and 200 SX Class 9-16-80. Circulated 257 SX.
measured and Drilled to 45.5# K-55 4797' ceme C Neat cer WOC 18 hr.	nated date of starting an true vertical depths for a 5 10-3/4" casing ented with 3400 S ment. Plugged do . Tested casing	y proposed work. If well I markers and zones perf and ran 1295' of and 2643' of 40. SX Lite cement wi own at 9:30 a.m. with 2000# for 3	is directionally drilled, give subsurface locations and tinent to this work.)* 51# K-55 10-3/4" casing, 1098' of 5# K-55 10-3/4" casing set at ith additives and 200 SX Class 9-16-80. Circulated 257 SX.
measured and Drilled to 45.5# K-55 4797' ceme C Neat cer WOC 18 hr. to 9-1/2"	nated date of starting an true vertical depths for a 5 10-3/4" casing ented with 3400 S ment. Plugged do . Tested casing and resumed dril	y proposed work. If well I markers and zones perf and ran 1295' of and 2643' of 40. SX Lite cement wi own at 9:30 a.m. with 2000# for 3 lling.	is directionally drilled, give subsurface locations and tinent to this work.)* 51# K-55 10-3/4" casing, 1098' of 5# K-55 10-3/4" casing set at ith additives and 200 SX Class 9-16-80. Circulated 257 SX. 30 min. Test OK. Reduced hole
measured and Drilled to 45.5# K-55 4797' ceme C Neat cer WOC 18 hr. to 9-1/2"	nated date of starting an true vertical depths for a 5 10-3/4" casing ented with 3400 S ment. Plugged do . Tested casing	y proposed work. If well I markers and zones perf and ran 1295' of and 2643' of 40. SX Lite cement wi own at 9:30 a.m. with 2000# for 3 lling.	is directionally drilled, give subsurface locations and tinent to this work.)* 51# K-55 10-3/4" casing, 1098' of 5# K-55 10-3/4" casing set at ith additives and 200 SX Class 9-16-80. Circulated 257 SX.
measured and Drilled to 45.5# K-55 4797' ceme C Neat cer WOC 18 hr. to 9-1/2" 0+2-USGS,	hated date of starting an true vertical depths for a 5 10-3/4" casing ented with 3400 S ment. Plugged do . Tested casing and resumed dril H 1-Hou	y proposed work. If well I markers and zones perf and ran 1295' of and 2643' of 40. SX Lite cement wi own at 9:30 a.m. with 2000# for 3 lling. 1-Susp 1-L	is directionally drilled, give subsurface locations and tinent to this work.)* 51# K-55 10-3/4" casing, 1098' of 5# K-55 10-3/4" casing set at ith additives and 200 SX Class 9-16-80. Circulated 257 SX. 30 min. Test OK. Reduced hole -BG 1-W. Stafford, Hou
measured and Drilled to 45.5# K-55 4797' ceme C Neat cer WOC 18 hr. to 9-1/2" 0+2-USGS,	nated date of starting an true vertical depths for a 5 10-3/4" casing ented with 3400 S ment. Plugged do . Tested casing and resumed dril	y proposed work. If well I markers and zones perf and ran 1295' of and 2643' of 40. SX Lite cement wi own at 9:30 a.m. with 2000# for 3 lling. 1-Susp 1-L	is directionally drilled, give subsurface locations and tinent to this work.)* 51# K-55 10-3/4" casing, 1098' of 5# K-55 10-3/4" casing set at ith additives and 200 SX Class 9-16-80. Circulated 257 SX. 30 min. Test OK. Reduced hole -BG 1-W. Stafford, Hou
measured and Drilled to 45.5# K-55 4797' ceme C Neat cer WOC 18 hr. to 9-1/2" 0+2-USGS, Subsurface Safety V	hated date of starting an true vertical depths for a 5 10-3/4" casing ented with 3400 S ment. Plugged do . Tested casing and resumed dril H 1-Hou	y proposed work. If well I markers and zones perf and ran 1295' of and 2643' of 40. SX Lite cement wi bwn at 9:30 a.m. with 2000# for 3 lling. 1-Susp 1-L	is directionally drilled, give subsurface locations and tinent to this work.)* 51# K-55 10-3/4" casing, 1098' of 5# K-55 10-3/4" casing set at ith additives and 200 SX Class 9-16-80. Circulated 257 SX. 30 min. Test OK. Reduced hole -BG 1-W. Stafford, Hou
measured and Drilled to 45.5# K-55 4797' ceme C Neat cer WOC 18 hr. to 9-1/2" 0+2-USGS, Subsurface Safety V	hated date of starting an true vertical depths for a 5 10-3/4" casing ented with 3400 S ment. Plugged do Tested casing and resumed dril H 1-Hou Valve: Manu, and Type what the togegoing is true	y proposed work. If well I markers and zones perf and ran 1295' of and 2643' of 40. SX Lite cement wi bwn at 9:30 a.m. with 2000# for 3 lling. 1-Susp 1-L	is directionally drilled, give subsurface locations and tinent to this work.)* 51# K-55 10-3/4" casing, 1098' of 5# K-55 10-3/4" casing set at ith additives and 200 SX Class 9-16-80. Circulated 257 SX. 30 min. Test OK. Reduced hole -BG 1-W. Stafford, Hou
measured and Drilled to 45.5# K-55 4797' ceme C Neat cer WOC 18 hr. to 9-1/2" 0+2-USGS, Subsurface Safety V 18. I hereby certify	hated date of starting an true vertical depths for a 5 10-3/4" casing ented with 3400 S ment. Plugged do . Tested casing and resumed dril H 1-Hou Valve: Manu and Type hat the oregoing is true ACCEPTED FOR RECO	y proposed work. If well Il markers and zones perf and ran 1295' of and 2643' of 40. SX Lite cement wi bwn at 9:30 a.m. with 2000# for 3 lling. I-Susp 1-L and correct TITLE Ast. Adm. DRDspate for Federal or Stat	<pre>is directionally drilled, give subsurface locations and tinent to this work.)* 51# K-55 10-3/4" casing, 1098' of .5# K-55 10-3/4" casing set at ith additives and 200 SX Class 9-16-80. Circulated 257 SX. 30 min. Test OK. Reduced hole </pre>
measured and Drilled to 45.5# K-55 4797' ceme C Neat cer WOC 18 hr. to 9-1/2" 0+2-USGS, Subsurface Safety V 18. I hereby certify	ACCEPTED FOR BECO	y proposed work. If well Il markers and zones perf and ran 1295' of and 2643' of 40. SX Lite cement wi bwn at 9:30 a.m. with 2000# for 3 lling. I-Susp 1-L and correct TITLE Ast. Adm. DRDspace for Federal or State	<pre>is directionally drilled, give subsurface locations and tinent to this work.)* 51# K-55 10-3/4" casing, 1098' of .5# K-55 10-3/4" casing set at ith additives and 200 SX Class 9-16-80. Circulated 257 SX. 30 min. Test OK. Reduced hole </pre>
measured and Drilled to 45.5# K-55 4797' ceme C Neat cer WOC 18 hr. to 9-1/2" 0+2-USGS, Subsurface Safety V 18. I hereby certify SIGNED APPROVED BY	ACCEPTED FOR BECC	y proposed work. If well I markers and zones perf and ran 1295' of and 2643' of 40. SX Lite cement wi bwn at 9:30 a.m. with 2000# for 3 lling. 1-Susp 1-L and correct TITLE Ast. Adm.	<pre>is directionally drilled, give subsurface locations and tinent to this work.)* 51# K-55 10-3/4" casing, 1098' of .5# K-55 10-3/4" casing set ut ith additives and 200 SX Class 9-16-80. Circulated 257 SX. 30 min. Test OK. Reduced hole </pre>

5