		- /	
Form 9–331	N.M. PC.D. COIY	Eile :	- مند
orm 9–331 Dec. 1973		Form Approved. Budget Bureau No. 42-R1424	
	UNITED STATES	5. LEASE	
	DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	LC-029392-B 6. IF INDIAN, ALLOTTEE OR TRIBE NAME	сана С., с. с. С., с. с.
SUNDRY	NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME	
Do not use this fo		t Greenwood Pregrayburg Unit Fed. F Com. 8. FARM OR LEASE NAME	- •
1. oil well	gas weli 🕅 other	Greenwood Pregrayburg Unit Fed. F Com. 9. WELL NO.	177
2. NAME OF	OPERATOR roduction Company√	10. FIELD OR WILDCAT NAME	
	OF OPERATOR		ينيون په بېرون
P. O. Bo	ox 68 Hobbs, NM 88240	11. SEC., T., R., M., OR BLK. AND SURVEY OR	
4. LUCATION below.)	OF WELL (REPORT LOCATION CLEARLY. See space 17	26-18-31	-
	ROD. INTERVAL: (Unit L, NW/4, SW/4)	12. COUNTY OR PARISH 13. STATE Eddy NM	<u>.</u>
AT TOTAL		14. API NO.	
	PROPRIATE BOX TO INDICATE NATURE OF NOTICE OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)	
-	APPROVAL TO: SUBSEQUENT REPORT OF:	3651.8 GL	
FEST WATER S			
SHOOT OR AC		EIVED RECEIVED	
REPAIR WELL		(NOTE: Report results of multiple completion or zone	
ULL OR ALTE		1980 ^{change on Form} NOV 1 4 1980	2-3-4-4 (5-6-4)
HANGE ZONE	s n		14.
BANDON* other)		ICAL SURVEY O. C. D.	
			100 mar 10
		EW MEXICO APTESIA, OFFICE	1. A. A. A.
17. DESCRIBE including e	PROPOSED OR COMPLETED OPERATIONS (Clearly st. estimated date of starting any proposed work. If well is and true vertical depths for all markers and zones pertin	ate all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and	
17. DESCRIBE including e measured a	PROPOSED OR COMPLETED OPERATIONS (Clearly statistimated date of starting any proposed work. If well is and true vertical depths for all markers and zones pertin	ate all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)*	
17. DESCRIBE including e measured a	PROPOSED OR COMPLETED OPERATIONS (Clearly sti- istimated date of starting any proposed work. If well is and true vertical depths for all markers and zones pertin to a TD of 12004' and ran 7015' of	ate all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)* 29.7# S-95 7-5/8" casing, 1327' of	
17. DESCRIBE including e measured a Drilled 26.4# S-	PROPOSED OR COMPLETED OPERATIONS (Clearly st. estimated date of starting any proposed work. If well is and true vertical depths for all markers and zones pertin to a TD of 12004' and ran 7015' of -95 7-5/8" casing, 1246' of 26.4# SS-	ate all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)* 29.7# S-95 7-5/8" casing, 1327' of 95 7-5/8" casing, and 2416' of	
7. DESCRIBE including e measured Drilled 26.4# S- 26.4# N-	PROPOSED OR COMPLETED OPERATIONS (Clearly statistimated date of starting any proposed work. If well is and true vertical depths for all markers and zones pertinent to a TD of 12004' and ran 7015' of -95 7-5/8" casing, 1246' of 26.4# SS80 7-5/8" casing set at 12004'. Cem	ate all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)* 29.7# S-95 7-5/8" casing, 1327' of 95 7-5/8" casing, and 2416' of mented with 1500 SX Lite cement	
Drilled 26.4# N- with ado Top of c	PROPOSED OR COMPLETED OPERATIONS (Clearly statistimated date of starting any proposed work. If well is and true vertical depths for all markers and zones pertinent to a TD of 12004' and ran 7015' of -95 7-5/8" casing, 1246' of 26.4# SS80 7-5/8" casing set at 12004'. Cem ditives and 500 SX Class H cement witteement at approx. 4535'. WOC 18 hr.	ate all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)* 29.7# S-95 7-5/8" casing, 1327' of 95 7-5/8" casing, and 2416' of mented with 1500 SX Lite cement h additives. Ran temp survey. Tested casing with 1500# for 30	
17. DESCRIBE including e measured 26.4# S- 26.4# N- with ado Top of c	PROPOSED OR COMPLETED OPERATIONS (Clearly statistimated date of starting any proposed work. If well is and true vertical depths for all markers and zones pertin to a TD of 12004' and ran 7015' of -95 7-5/8" casing, 1246' of 26.4# SS- -80 7-5/8" casing set at 12004'. Cem ditives and 500 SX Class H cement wit	ate all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)* 29.7# S-95 7-5/8" casing, 1327' of 95 7-5/8" casing, and 2416' of mented with 1500 SX Lite cement h additives. Ran temp survey. Tested casing with 1500# for 30	
Drilled 26.4# N- with ado Top of c	PROPOSED OR COMPLETED OPERATIONS (Clearly statistimated date of starting any proposed work. If well is and true vertical depths for all markers and zones pertin to a TD of 12004' and ran 7015' of -95 7-5/8" casing, 1246' of 26.4# SS80 7-5/8" casing set at 12004'. Cem ditives and 500 SX Class H cement witt cement at approx. 4535'. WOC 18 hr.	ate all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)* 29.7# S-95 7-5/8" casing, 1327' of 95 7-5/8" casing, and 2416' of mented with 1500 SX Lite cement h additives. Ran temp survey. Tested casing with 1500# for 30	
Drilled 26.4# N- with ado Top of c	PROPOSED OR COMPLETED OPERATIONS (Clearly statistimated date of starting any proposed work. If well is and true vertical depths for all markers and zones pertin to a TD of 12004' and ran 7015' of -95 7-5/8" casing, 1246' of 26.4# SS80 7-5/8" casing set at 12004'. Cem ditives and 500 SX Class H cement witt cement at approx. 4535'. WOC 18 hr.	ate all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)* 29.7# S-95 7-5/8" casing, 1327' of 95 7-5/8" casing, and 2416' of mented with 1500 SX Lite cement h additives. Ran temp survey. Tested casing with 1500# for 30	
Drilled 26.4# S- 26.4# N- with ado Top of c min. Te	PROPOSED OR COMPLETED OPERATIONS (Clearly statistimated date of starting any proposed work. If well is and true vertical depths for all markers and zones pertin to a TD of 12004' and ran 7015' of -95 7-5/8" casing, 1246' of 26.4# SS80 7-5/8" casing set at 12004'. Cem ditives and 500 SX Class H cement witt cement at approx. 4535'. WOC 18 hr.	ate all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)* 29.7# S-95 7-5/8" casing, 1327' of 95 7-5/8" casing, and 2416' of mented with 1500 SX Lite cement th additives. Ran temp survey. Tested casing with 1500# for 30 resumed drilling.	
17. DESCRIBE including e measured 26.4# S- 26.4# N- with add Top of c min. Te 0+4-USGS	PROPOSED OR COMPLETED OPERATIONS (Clearly statistimated date of starting any proposed work. If well is and true vertical depths for all markers and zones pertine 4.5 The state of the starting state of the state of	ate all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)*29.7# S-95 7-5/8" casing, 1327' of 95 7-5/8" casing, and 2416' of lented with 1500 SX Lite cement h additives. Ran temp survey. Tested casing with 1500# for 30 resumed drilling.1-LBG1-W. Stafford, Hou	
17. DESCRIBE including e measured 26.4# S- 26.4# N- with add Top of c min. Te 0+4-USGS	PROPOSED OR COMPLETED OPERATIONS (Clearly sta estimated date of starting any proposed work. If well is and true vertical depths for all markers and zones pertin -95 7-5/8" casing, 1246' of 26.4# SS- -80 7-5/8" casing set at 12004'. Cem ditives and 500 SX Class H cement wit cement at approx. 4535'. WOC 18 hr. est OK. Reduced hole to 6-1/2" and r	ate all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)*29.7# S-95 7-5/8" casing, 1327' of 95 7-5/8" casing, and 2416' of lented with 1500 SX Lite cement h additives. Ran temp survey. Tested casing with 1500# for 30 resumed drilling.1-LBG1-W. Stafford, Hou	
17. DESCRIBE including e measured 26.4# S- 26.4# N- with add Top of c min. Te 0+4-USGS Subsurface Safe	PROPOSED OR COMPLETED OPERATIONS (Clearly sti- estimated date of starting any proposed work. If well is and true vertical depths for all markers and zones pertin -95 7-5/8" casing, 1246' of 26.4# SS- -80 7-5/8" casing set at 12004'. Cem ditives and 500 SX Class H cement wit cement at approx. 4535'. WOC 18 hr. est OK. Reduced hole to 6-1/2" and r	ate all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)* 29.7# S-95 7-5/8" casing, 1327' of 95 7-5/8" casing, and 2416' of 195 7-5/8" casing, and 2416' of 100 SX Lite cement ate all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)* 29.7# S-95 7-5/8" casing, and 2416' of 195 7-5/8" casing, and 2416' of 195 7-5/8" casing, and 2416' of 100 SX Lite cement ate all pertinent dates, directly and 2416' of 1500 SX Lite cement beneted with 1500 SX Lite cement beneted casing with 1500# for 30 resumed drilling. 1-LBG 1-W. Stafford, Hou Set @Ft.	
17. DESCRIBE including e measured 26.4# S- 26.4# N- with add Top of c min. Te 0+4-USGS Subsurface Safe	PROPOSED OR COMPLETED OPERATIONS (Clearly sti- istimated date of starting any proposed work. If well is and true vertical depths for all markers and zones pertin to a TD of 12004' and ran 7015' of -95 7-5/8" casing, 1246' of 26.4# SS- -80 7-5/8" casing set at 12004'. Cem- ditives and 500 SX Class H cement with cement at approx. 4535'. WOC 18 hr. est OK. Reduced hole to 6-1/2" and r S, H 1-Hou 1-Susp ety Valve: Manu. and Type	ate all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)* 29.7# S-95 7-5/8" casing, 1327' of 95 7-5/8" casing, and 2416' of 195 7-5/8" casing, and 2416'	
17. DESCRIBE including e measured 26.4# S- 26.4# N- with add Top of c min. Te 0+4-USGS Subsurface Safe 18. I herebyce SIGNED	PROPOSED OR COMPLETED OPERATIONS (Clearly sti- istimated date of starting any proposed work. If well is and true vertical depths for all markers and zones pertin to a TD of 12004' and ran 7015' of -95 7-5/8" casing, 1246' of 26.4# SS- -80 7-5/8" casing set at 12004'. Cem ditives and 500 SX Class H cement with cement at approx. 4535'. WOC 18 hr. est OK. Reduced hole to 6-1/2" and r S, H 1-Hou 1-Susp ety Valve: Manu. and Type	ate all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)* 29.7# S-95 7-5/8" casing, 1327' of 95 7-5/8" casing, and 2416' of 195 7-5/8" casing, and 2416'	
17. DESCRIBE including e measured 26.4# S- 26.4# N- with add Top of c min. Te 0+4-USGS Subsurface Safe 18. I herebyce SIGNED	PROPOSED OR COMPLETED OPERATIONS (Clearly sti- stimated date of starting any proposed work. If well is and true vertical depths for all markers and zones pertin to a TD of 12004' and ran 7015' of -95 7-5/8" casing, 1246' of 26.4# SS- -80 7-5/8" casing set at 12004'. Cem ditives and 500 SX Class H cement wit cement at approx. 4535'. WOC 18 hr. est 0K. Reduced hole to 6-1/2" and r st 0K. Reduced hole to 6-1/2" and r best 0K. Reduced hole to 6-1/2" and r st 0K. Reduced hole to 6-1/2" and r	ate all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)* 29.7# S-95 7-5/8" casing, 1327' of 95 7-5/8" casing, and 2416' of 95 7-5/8" casing, and 2416' of 95 7-5/8" casing, and 2416' of 96 1000 SX Lite cement 1000 the second the second temp survey. Tested casing with 1500# for 30 resumed drilling. 1-LBG 1-W. Stafford, Hou Set @ Ft. Analystare 11-4-80 office use) 11-4-80	
17. DESCRIBE including e measured 26.4# S- 26.4# N- with add Top of c min. Te 0+4-USGS Subsurface Safe 18. I herebyce SIGNED	PROPOSED OR COMPLETED OPERATIONS (Clearly st. istimated date of starting any proposed work. If well is and true vertical depths for all markers and zones pertin to a TD of 12004' and ran 7015' of -95 7-5/8" casing, 1246' of 26.4# SS- -80 7-5/8" casing set at 12004'. Cem ditives and 500 SX Class H cement wit cement at approx. 4535'. WOC 18 hr. est OK. Reduced hole to 6-1/2" and r S, H 1-Hou 1-Susp ety Valve: Manu. and Type rtify that the diregoing is true and correct 	ate all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)* 29.7# S-95 7-5/8" casing, 1327' of 95 7-5/8" casing, and 2416' of 195 7-5/8" casing, and 2416' of 195 7-5/8" casing, and 2416' of 195 7-5/8" casing with 1500 \$\$ Lite cement the additives. Ran temp survey. Tested casing with 1500# for 30 resumed drilling. 1-LBG 1-W. Stafford, Hou	
17. DESCRIBE including e measured 26.4# S- 26.4# N- with add Top of c min. Te 0+4-USGS Subsurface Safe 18. I herebyce SIGNED	PROPOSED OR COMPLETED OPERATIONS (Clearly sti- stimated date of starting any proposed work. If well is and true vertical depths for all markers and zones pertin to a TD of 12004' and ran 7015' of -95 7-5/8" casing, 1246' of 26.4# SS- -80 7-5/8" casing set at 12004'. Cem ditives and 500 SX Class H cement wit cement at approx. 4535'. WOC 18 hr. est OK. Reduced hole to 6-1/2" and r st OK. Reduced hole to 6-1/2" and r of the fregoing is true and correct tify that the fregoing is true and correct 	ate all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)* 29.7# S-95 7-5/8" casing, 1327' of 95 7-5/8" casing, and 2416' of 195 7-5/8" casing, and 2416' of 195 7-5/8" casing, and 2416' of 195 7-5/8" casing with 1500 \$\$ Lite cement the additives. Ran temp survey. Tested casing with 1500# for 30 resumed drilling. 1-LBG 1-W. Stafford, Hou	

. . . .