

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-73

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	☒
FILE	☒
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	State ☒ For ☐
5. State Oil & Gas Lease No.	E-1051

SUNDARY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT DEPTH. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

RECEIVED

1. OIL WELL ☐ GAS WELL ☒ OTHER- ☐	7. Unit Agreement Name North Millman
2. Name of Operator Yates Petroleum Corporation ✓	8. Farm or Lease Name North Millman Unit
3. Address of Operator 207 South 4th Street - Artesia, NM 83210	9. Well No. 2
4. Location of Well UNIT LETTER <u>G</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>8</u> TOWNSHIP <u>19S</u> RANGE <u>28E</u>	10. Field and Pool, or Wildcat Unit. South Millman MOR
15. Elevation (Show whether DF, RT, GR, etc.) 3544' GR	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:
REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☒
CASING TEST AND CEMENT JOBS ☒
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 17½" hole at 3:30 PM 7-16-80.

TD 406' - Ran 13 joints of 13-3/8" 54# ST&C (374') of casing set at 372'.
1-Texas Pattern guide shoe at 372'. Insert float at 332'. Cemented w/400
sacks of Class C 4% CaCl. Slurry weight 14.8, 1.32 cu ft/sack. Compressive
Strength at 70 degrees 1032 psi in 12 hours. PD 8:45 AM 7-17-80. Cement
circulated 30 sacks to the surface. WOC 12 hours, NU and backed off, tested
to 1500# OK, reduced hole to 12½", drilled plug, tested to 600# OK and resumed
drilling.

TD 2300' - Ran 57 joints of 8-5/8" 24# ST&C (2299') of casing set at 2298'.
1-Insert float at 2258'. Cemented w/1025 sacks 65/35 Poz, 8# Kolite, 1/4#
celloflakes and 3% CaCl. Tailed in w/150 sacks Class C 2% CaCl. PD 12:17
PM 7-22-80. Circulated 50 sacks of cement to the surface. WOC 18 hours,
NU, tested to 1500# OK, reduced hole to 7-/78", drilled plug, tested to
600# OK and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Tomlinson TITLE Geol. Secty DATE 7-30-80

APPROVED BY M. K. Williams TITLE OIL AND GAS INSPECTOR DATE JUL 31 1980

CONDITIONS OF APPROVAL, IF ANY: