

clsf
up

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-23409
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. E-1051
7. Lease Name or Unit Agreement Name North Millman Unit
8. Well No. 2
9. Pool name or Wildcat Millman Strawn/Millman Morrow
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3544' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter <u>G</u> : <u>1980</u> Feet From The <u>North</u> Line and <u>1980</u> Feet From The <u>East</u> Line Section <u>8</u> Township <u>19S</u> Range <u>28E</u> NMPM <u>Eddy</u> County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3544' GR	

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: Re-perforate Morrow and frac perfs. ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Well is presently completed in the Morrow from 10891-10926', 10986-10990' and Strawn 9720-9914'. Propose to go in and reperforate the Morrow and frac as needed as follows:

1. Move in and rig up. Load casing with clean KCL water. TOOH w/pump & rods and tubing. RIH w/frac string and latch onto on/off tool on packer at 10677'. Swab tubing as necessary to pull standing valve from packer.
2. Reperforate Morrow from 10891-10926' w/22 holes (2 SPF). Frac Morrow perfs. 10891-10926', 10986-10990' with 70 Quality foam/binary foam and 25000-30000# dual resin coated sand or IDP.
3. Flow & swab test Morrow.
4. Will ultimately commingle Morrow and Strawn and will submit new allocations for each zone depending on Morrow test results.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Production Clerk DATE July 21, 1992
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY

DAKE WILLIAMS

APPROVED BY SUPERVISOR, DISTRICT II TITLE DATE JUL 26 1993

CONDITIONS OF APPROVAL, IF ANY: