

IL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

RECEIVED

OCT 7 1980

O. C. D.

ARTESIA OFFICE

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.O.I.	
LAND OFFICE	
OPERATOR	1

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
2. Name of Operator Yates Petroleum Corporation ✓	5. State Oil & Gas Lease No. OG-783
3. Address of Operator 207 So. 4th St., Artesia, NM 88210	7. Unit Agreement Name
4. Location of Well UNIT LETTER C 990 FEET FROM THE North LINE AND 2310 FEET FROM THE West LINE, SECTION 5 TOWNSHIP 19S RANGE 25E NMPM.	8. Farm or Lease Name Greasewood BD State
	9. Well No. 10
	10. Field and Pool, or Wildcat, Assoc. Penasco Draw SA Yeso
15. Elevation (Show whether DF, RT, GR, etc.) 3583' GR	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/> prod. casing, perforate & treat

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 3150' Ran 77 joints of 4-1/2" 9.5# J-55 casing set at 3124'. 1-guide shoe at 3124'. Cemented w/375 sacks 50-50 Poz, .3% D-108, .2% D-65 and 3# KCL. PD 2:00 PM 9-11-80. WOC and tested to 1500#, OK. WIH w/Steel Strip gun on wireline and perforated 2648-2757' w/11 .50" holes as follows: 2648, 50, 52, 54, 56, 58, 60, 63, 65, 2754½ & 57'. WIH w/tbg and spotted acid. Treated perforations w/1500 gallons 15% acid and 30000 gallons gelled 1% KCL water, 45000# sand. Flowed well down to perforate second stage. WIH w/Steel Strip gun on wireline and perforated 2456-2571' w/11 .50" holes as follows: 2456, 73, 74½, 2522, 24, 27, 29, 31, 66, 69½ & 71'. WIH w/bridge plug and set at 2608'. Spotted acid over perfs. Treated perforations w/1500 gallons 15% acid, 30000 gallons gelled 1% KCL water and 45000# sand.

The Bridge plug @ 2608 was pulled.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Albert R. Hall TITLE Engineer DATE October 3, 1980

APPROVED BY W.A. Gressett TITLE SUPERVISOR, DISTRICT II DATE OCT 9 1980

CONDITIONS OF APPROVAL, IF ANY: