

NO. OF COPIES RECEIVED	5
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

O. C. D.
ARTISIA OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. L-4893
7. Unit Agreement Name
8. Farm or Lease Name Parkway "B" State
9. Well No. 1
10. Field and Pool, or Wildcat Wildcat (Wolfcamp)
12. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Southland Royalty Company ✓
3. Address of Operator 1100 Wall Towers West, Midland, Texas 79701
4. Location of Well UNIT LETTER I, 1980 FEET FROM THE south LINE AND 660 FEET FROM THE east LINE, SECTION 15 TOWNSHIP 19S RANGE 29E N.M.P.M.
15. Elevation (Show whether DF, RT, GR, etc.) 3306'GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud 15" hole 9:00 P.M. 8-5-80. Drill 15" to 248'. CCM to run csg. Ran 6 jcs. 11 3/4" 42# H-40 ST&C csg. Set @ 248'. Cmt w/300 sxs. Class "C" w/2% cc. Filled back side of 11 3/4" csg w/16 yd. ready mix concrete. WOC 18 hrs. Install 11 3/4" x 12" 3000# head. Install BOP. After 24 hrs. pressure test BOP & 11 3/4" csg to 1000# for 30 min. Held okay. Drill ahead w/11" bit.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Donald R Cray

TITLE District Operation Engineer

DATE 8-13-80

APPROVED BY W. A. Gussett

TITLE SUPERVISOR, DISTRICT II

DATE AUG 19 1980

CONDITIONS OF APPROVAL, IF ANY: