

Form 9-111
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

Sorenson - #12264
6. IF INDIAN, ALLOTTEE OR TRIBE NAME7. UNIT AGREEMENT NAME
Lake McMillan Federal Unit

8. FARM OR LEASE NAME

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 30-T19S-R27E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Gulf Oil Corporation ✓

3. ADDRESS OF OPERATOR

P. O. Box 670, Hobbs, NM 88240

O. C. D.
ARTESIA, OFFICE

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below.)
At surface

1450' FSL & 150' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DE, RT, GR, etc.)

3324' GL

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐

Casing

REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

X

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Ard Drilling Co. spudded 17½" surface hole at 8:30 P.M., 8-12-80. Drilled to 322'.
 Ran 7 joints & 1 cut joint 13-3/8" 48# H-40 ST&C (305') set at 322', FC at 284'.
 Cement with 200 sacks thick set & 200 sacks Class "H" 2% CaCl₂. Plug down at 5 A.M.,
 8-13-80. WOC 18 hours. Circulate cement. Test casing & BOP to 2000#. Drill plug,
 float & cement. Started drilling 12½" hole at 4:30 P.M., 8-15-80.

ACCEPTED FOR RECORD

D.W. Chester

SEP 8 1980

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Area Drilling Supt.

DATE

8-22-80

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: