N.M.O.C.D. COPY

Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.
Sorensen - 12264

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL [ ] GAS WELL [X] OTHER

7. UNIT AGREEMENT NAME
Lake McMillan Federal Unit

2. NAME OF OPERATOR
Gulf Oil Corporation

8. FARM OR LEASE NAME

3. ADDRESS OF OPERATOR
P. O. Box 670, Hobbs, NM 88240

9. WELL NO.
1

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1450' FSL & 150' FEL

10. FIELD AND POOL, OR WILDCAT
Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 30-T19S-R27E

12. COUNTY OR PARISH
Eddy

13. STATE
NM

14. API NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3324' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

WATER SHUT-OFF	[ ]	PULL OR ALTER CASING	[ ]
FRACTURE TREAT	[ ]	MULTIPLE COMPLETE	[ ]
SHOOT OR ACIDIZE	[ ]	ABANDON*	[ ]
REPAIR WELL	[ ]	CHANGE PLANS	[ ]
(Other)			

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	[ ]	REPAIRING WELL	[ ]
FRACTURE TREATMENT	[ ]	ALTERING CASING	[ ]
SHOOTING OR ACIDIZING	[ ]	ABANDONMENT*	[ ]
(Other) Perfd, Acid			X

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Clean & clear location, set anchors, pipe valves out of cellar. Perf 7870-76' & 7886-96' with ½" o-phase decentralized bullets JM. Acidize 7870-96' with 6000 gals 20% NEFE HCL & (3%) 1/2# BAF's. Flush with 2% check KCL & surfactants. Max pres 4500#, min 3800#, avg BPM 8.4, avg pres 4333#, ISIP 1000#, 15 min 800#. Complete after drilling, perfg & acidizing 11-30-80.

18. I hereby certify that the foregoing is true and correct

SIGNED [signature] TITLE Area Engineer DATE

(This space for Federal or State office use)

APPROVED BY TITLE DATE
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD
GS
DEC 11 1980
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO