

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates Petro corp.</u>		Lease <u>Rathum OC St.com.</u>		Well # <u>1</u>	
Location of Well	Unit <u>E</u>	Section <u>32</u>	Township <u>19</u>	Range <u>21</u>	County <u>Eddy</u>
Drilling Contractor	<u>2015' FNL</u> <u>660' x</u> <u>Capitan #14</u> <u>Moranco #9</u>		Type of Equipment <u>Rotary</u>		
<u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2</u>	<u>13 3/8</u>			<u>80'</u>	<u>Ready-Mix</u>
<u>*12 1/4</u>	<u>8 5/8</u>			<u>1400'</u>	<u>750 sx</u>
<u>7 7/8</u>	<u>4 1/2 or 5 1/2</u>	<u>17# 15.5</u> <u>11.6# 10.5</u>		<u>7710'</u>	<u>500 sx</u>
Casing Data:					
Surface <u> </u> joints of <u>8 5/8"</u> inch <u>24</u> # Grade <u>K-55</u>					
<u>(Approved)</u> (Rejected)					
Inspected by <u>M.S.</u> date <u>10/16/80</u>					
Cementing Program					
Size of hole <u>12 1/4"</u> Size of Casing <u>8 5/8"</u> Sacks cement required <u> </u>					
Type of Shoe used <u>guide</u> Float collar used <u>inner</u> Btm 3 jts welded <u>yes</u>					
TD of hole <u>1427'</u> Set <u>1427'</u> Feet of <u>8 5/8"</u> inch <u>24</u> # Grade <u>J-55</u>					
<u>(New)</u> used csg. @ <u>1427'</u> with <u>1502 cc</u> sacks neat cement around shoe					
+ <u>200</u> sax <u>C</u> additives <u>370 cc</u>					
Plug down @ <u>1200</u> <u>(AM)</u> (PM) Date <u>10/22/80</u>					
Cement circulated <u>No</u> No. of Sacks <u>-0-</u>					
Cemented by <u>Dowell</u> Witnessed by <u>Mike Stubblefield</u>					
Temp. Survey ran @ <u>600</u> <u>(AM)</u> (PM) Date <u>10/22/80</u> top cement @ <u>525'</u>					
Casing test @ <u> </u> (AM) (PM) Date <u> </u>					
Method Used <u> </u> Witnessed by <u> </u>					
Checked for shut off @ <u> </u> (AM) (PM) Date <u> </u>					
Method used <u> </u> Witnessed by <u> </u>					
Remarks: <u> </u>					
<u>Baskets @ 431'-561'-955</u>					
<u>No centralizers</u>					
<u>last circ. @ 190'-327'-496'-950'</u>					
<u>last dily break @ 1320'</u>					