

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

OCT 30 1980

AMENDED REPORT

O. C. D.
ARTESIA, OFFICE

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.B.	
LAND OFFICE	
OPERATOR	1

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT - (FORM C-103) FOR SUCH PROPOSALS.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐	7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation ✓	8. Farm or Lease Name Latham OC State Com
3. Address of Operator 207 South 4th St., Artesia, NM 88210	9. Well No. 1
4. Location of Well UNIT LETTER <u>E</u> <u>2015</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>32</u> TOWNSHIP <u>19S</u> RANGE <u>21E</u> NMPM.	10. Field and Pool, or Wildcat Wildcat Morrow
11. Elevation (Show whether DF, RT, GR, etc.) 4541' GR	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 17-1/2" hole at 7:45 AM 10-14-80.

TD 131' Ran 3 joints of 13-3/8" 48# 8rd ST&C K-55 casing set a 93'. 1-Texas Pattern guide shoe at 93'. Flapper float at 83'. Cemented w/150 sacks Class "C" 4% CaCl. Slurry weight 14.8, 1.32 cu ft/sack. Compressive strenght at 70 degrees 1023 psi in 12 hours. PD 8:30 AM 10-15-80. Cement circulated 20 sacks to pit. WOC 12 hours. Reduced hole to 12-1/4".

Drilled plug and tested to 600#, OK. Resumed drilling.

TD 1427' Ran 34 joints of 8-5/8" 24# J-55 ST&C casing set at 1427'. 1-Texas Pattern guide shoe at 1427'. Flapper insert float at 1385'. Cemented w/200 sacks Class "C" Neat, 1200 sacks 65-35 Poz, 4% Bentonite, 8# Kolite, 1/4# celloflakes & 3% CaCl. Tailed in w/150 sacks Class "C" 2% CaCl. PD 12:00 midnight 10-21-80. Cement didnt-ciruclate. WOC 6 hours. Ran temperature survey and found top of cement at 525'. Ran 1". Tagged cement at 523'. Spotted 255 sacks Class "C" 4% CaCl. PD 10:30 AM 10-22-80. WOC 2 hours. Ran 1". Tagged cement at 523'. Spotted 50 sacks Class "C" 4% CaCl. PD 12:45 PM 10-22-80. WOC 2 hours. Ran 1". Tagged cement at 523'. Spotted 50 sacks Class "C" 4% CaCl. PD 2:45 PM 10-22-80. WOC 2 hrs. Ran 1". Tagged cement at 515'. Spotted 75 sacks Class "C" 4% CaCl. PD 5:30 PM 10-22-80. WOC 2 hours. Ran 1". Tagged cement at 410'. Spotted 50 sacks Class "C" 4% CaCl. PD 8:15 PM 10-22-80. WOC 2 hours. Ran 1". Tagged cement at 390'. Spotted 50 sacks Class "C" 4% CaCl. PD 10:45 PM 10-22-80. WOC 2 hours. Ran 1". Tagged cement at 310'. Spotted 50 sacks Class "C" 4% CaCl. PD 1:00 AM 10-23-80. WOC 2 hours. Ran 1". Tagged cement at 201'. (cont'd)

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Albert R. Hall TITLE Engineer DATE Oct. 29, 1980

APPROVED BY W. A. Gussitt TITLE SUPERVISOR, DISTRICT II DATE OCT 31 1980

CONDITIONS OF APPROVAL, IF ANY: