

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.O.S.	
LAND OFFICE	
OPERATOR	1

OCT 9 1980

O. C. D.
ARTESIA, OFFICE

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation ✓	6. Farm or Lease Name Nicholas BJ
3. Address of Operator 207 South 4th St., Artesia, NM 88210	9. Well No. 2
4. Location of Well UNIT LETTER <u>J</u> <u>2310</u> FEET FROM THE <u>South</u> LINE AND <u>2310</u> FEET FROM THE <u>East</u> LINE, SECTION <u>5</u> TOWNSHIP <u>19S</u> RANGE <u>25E</u> NMPM.	10. Field and Pool, or Wildcat, Assoc. Penasco Draw SA-Yeso
15. Elevation (Show whether DF, RT, GR, etc.) 3588.9' GR	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <u>Prod. Casing, Perforate & treat</u> <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 3500' Ran 87 joints of 4-1/2" 9.5# J-55 casing set at 3484'. 1-guide shoe at 3484'. Cemented w/425 sacks 50-50 Poz "C", 3/10% D-108, 2/10% D-65 and 3# KCL. PD 7:00 PM 10-1-80. Circulated 35 sacks to pit. WOC and tested to 1500#, OK.

WIH w/Steel Strip gun on wireline and perforated 2456-2696' w/16 .50" holes as follows: 2456, 59, 62, 2563, 66, 69, 72, 74, 2603, 06, 36, 39, 87, 90, 93 & 96'. Spotted acid and broke formation. Sand frac'd perforations 2456-2696' w/40000 gallons gelled 1% KCL water and 70000# sand (5000# 100 mesh and 65000# 20-40 sand).

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Albert R. Hall TITLE Engineer DATE October 8, 1980

APPROVED BY W.A. Gussert TITLE SUPERVISOR, DISTRICT II DATE OCT 10 1980

CONDITIONS OF APPROVAL, IF ANY: