

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-73

| | |
|------------------------|---|
| NO. OF COPIES RECEIVED | |
| DISTRIBUTION | |
| SANTA FE | 1 |
| FILE | 1 |
| U.S.O.S. | |
| LAND OFFICE | 1 |
| OPERATOR | |

NOV 05 1980

AMENDED REPORT*

5a. Indicate Type of Lease
State ☐ For ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator

Yates Petroleum Corporation² ✓

Address of Operator

207 South 4th St., Artesia, NM 88210

Location of Well

UNIT LETTER J 2310 FEET FROM THE South LINE AND 2310 FEET FROM
THE East LINE, SECTION 5 TOWNSHIP 19S RANGE 25E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name

Nicholas BJ

9. Well No.

2

10. Field and Pool, or Wildcat
Assoc. Penasco Draw-SA Yesso

15. Elevation (Show whether DF, RT, GR, etc.)

3588.9' GR

12. County

Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☒
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐
OTHER ☐

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 308' Spudded a 15" hole at 2:30 PM 9-18-80. Ran 8 joints of 10-3/4" 34.75" J-55 (308') of casing set at 308'. 1-cut-off shoe at 308'. Fla-per insert float at 266'. Cemented w/350 sacks Class "C" 4% CaCl. PD 9:45 PM 9-18-80. Cement circulated 35 sacks to pit. WOC 12 hours. Reduced hole to 9-1/2". Drilled plug and tested to 600 psi, OK. Resumed drilling.

TD 967' Ran 22 joints of 7" K-55 ST&C (962.29') of casing set at 965'. 1 shoe joint at 962'. Flapper float at 916'. 1 cement basket at 398'. Cemented w/200 sacks Class "C" Neat, 800 sacks 65-35 Poz, 4% Bentonite, 8# Keolite, 1/4# celloflakes and 3% CaCl. Tailed in w/150 sacks Class "C" 2% CaCl. PD 12:30 PM 9-21-80. Cement did not circulate. WOC 6 hours. Ran Temperature Survey and found top of cement at 360'. Ran 1". Tagged cement at 340'. *Spotted 50 sacks Class "C" 4% CaCl. PD 7:45 PM 9-21-80. WOC 2 hours. Ran 1". Tagged cement at 325'. Spotted 75 sacks Class "C" 4% CaCl. PD 10:00 PM 9-21-80. WOC 2 hours. Ran 1". Tagged cement at 312'. Spotted 100 sacks Class "C" 4% CaCl. PD 12:15 AM 9-22-80. Circulated 5 sacks to pit. WOC 18 hours. Nipped up and tested to 1500 psi, OK. Reduced hole to 6-1/4". Drilled plug and tested to 600 psi, OK. Resumed drilling.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Albert R. Hall

TITLE Engineer

DATE Nov. 5, 1980

APPROVED BY W.A. Gressett

TITLE SUPERVISOR, DISTRICT II

DATE NOV 12 1980

CONDITIONS OF APPROVAL, IF ANY: