

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

DEC 1 1980

C. C. D.

ARTESIA OFFICE

Form C-103
Revised 10-1-7

NO. OF COPIES RECEIVED	2
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☒ OTHER ☐

Name of Operator

Yates Petroleum Corporation ✓

Address of Operator

207 South 4th, Artesia, NM 88210

Location of Well

UNIT LETTER I, 1980 FEET FROM THE South LINE AND 660 FEET FROMTHE East LINE, SECTION 11 TOWNSHIP 19S RANGE 24E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)

3602' GR

5a. Indicate Type of Lease

State ☐Fee ☒

5. State Oil & Gas Lease No.

7. Unit Agreement Name

8. Farm or Lease Name

Davis NC Com

9. Well No.

1

10. Field and Pool, or Wildcat Und. Boyd Morrow

12. County

Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐PLUG AND ABANDON ☐REMEDIAL WORK ☐ALTERING CASING ☐TEMPORARILY ABANDON ☐COMMENCE DRILLING OPNS. ☐PLUG AND ABANDONMENT ☐PULL OR ALTER CASING ☐CHANGE PLANS ☐CASING TEST AND CEMENT JOBS ☒OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 17-1/2" hole at 10:30 AM 11-14-80.

TD 445' Ran 11 joints of 13-3/8" 48# H-40 casing set at 445'. 1-Texas Pattern guide show at 445'. Insert flapper float at 401'. Cemented w/455 sacks of Class C 4% CaCl. Slurry weight 14.8, 1.32 cu ft/sack. Compressive strength at 70 degrees 1023 psi in 12 hours. PD 1:45 AM 11-15-80. Cement did not circulate. Filled hole w/9 yards of Ready-Mix. WOC 12 hours. Backed off and reduced hole to 12-1/4". Drilled plug and tested to 600 psi, OK.

TD 938' Ran 23 joints of 8-5/8" 24# J-55 ST&C casing at 938'. 1-Texas Pattern guide shoe at 938'. Flapper float at 898'. Cemented w/600 sacks Howco Lite, 10# gilsonite, 1/4# celloflakes and 2% CaCl. Tailed in w/150 sacks Class C 2% CaCl. PD 6:45 AM 11-17-80. Cement circulated 40 sacks. WOC 18 hours. Nipped up and tested to 1500 psi, OK. Reduced hole to 7-7/8". Drilled plug and tested to 600 psi, OK. Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED

Albert R. Hall

TITLE

Engineer

DATE

12-1-80

APPROVED BY

W. A. Gussert

TITLE

SUPERVISOR, DISTRICT II

DATE

DEC 3 1980

CONDITIONS OF APPROVAL, IF ANY: