

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

RECEIVED

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Bravo Operating Company

3. Address and Telephone No.

P. O. Box 2160, Hobbs, N. M. 88241 505-397-3970

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FNL and 1980' FEL Section 30

5. Lease Designation and Serial No.

LC-062376

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Federal H.G. #1

9. API Well No.

30-015-23561

10. Field and Pool, or Exploratory Area

HG Morrow Gas

11. County or Parish, State

Eddy, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other

- ☒ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Change in Plug Back Procedure

- 1) Set CIBP @ 11,675' - spot 35' cement on top
- 2) Spot cement plug from 9600' - 9150'
- 3) Perforate @ 6150' - set retainer @ 6100'
- 4) Squeeze with 100 sx cement
- 5) Spot 35' cement on top of retainer @ 6100'
- 6) Perforate 4 holes @ 4300'
- 7) Set cement retainer @ 4275'. Circ cement outside 5-1/2" csg. up 5-1/2" x 8-5/8" annulus to est. top of 3400'
- 8) Perf, test, treat and evaluate Delaware Zone's as follows:  
4014-30'  
3950-65'  
3835-49'

We are requesting this to be a permanent abandonment of this well from 4275' to TD.

14. I hereby certify that the foregoing is true and correct

Signed

*Gary Conway*

Title Consultant

Date 12-8-92

(This space for Federal or State office use)

Approved by

*Robert H. Glass*

Title

Date 1-4-93

Conditions of Approval, if any: